

BRANTNER SINGLE-AXLE BACKBOARD TIPPER E 2520 R

10 YEARS WARRANTY ON CHASSIS FRAME

Permissible gross weight: 2,5 t, Payload. 1,9 t
Platform size outside:
2120 x 1260/1290 x 400 mm
25 km/h

Technical data approx.:

Permissible gross weight	2500 kg
Dead weight:	600 kg
Platform size inside:	2050 x 1210/1240 mm
Overall length:	3250 mm
Overall width:	1370 mm
Trailer height:	430 - 680 mm
Steel sideboards:	400 mm
Track:	1000 mm
Axle cross section:	55 mm
Platform height:	900 mm
Tyres:	10.0/75 - 15.3 (10)
Tipping cylinder stage	2
Stroke length:	600 mm
Cylinder diameter:	approx. 60 / 75 mm
Max. operating pressure	175 bar
Tipping angle rear:	approx. 50°
Required amount of oil	approx. 2,5 l

Euro without

VAT Art. Nr.

3.382,- 101 0000 **Basic price E 2520 R 25 km/h**
version Austria with changing brake

3.382,- 101 0001 **Basic price E 2520 R 25 km/h**
version Germany with parking brake

CHASSIS:

758,- 101 1060	Version as 3-side tipper
293,- 101 5120	Hand operated pump comb. with HD-connection
411,- 101	Version with overrun brake with moving automatism

BODY:

743,- 101 3130	Steel attachment boards 400 mm *)
79,- 101 3485	Grain slide rear
61,- 101 3460	Discharge channel not lockable
142,- 101 3470	Discharge channel with additional fine dosing for grain slide
934,- 102 3730	Leave grating attachment board 600 mm high

TYRES INSTEAD OF STANDARD TYRES:

80,- 101 8120	11.5/80 - 15.3 (10)
261,- 101 8125	12.5/80 - 15.3 (14)

SUPPORT FACILITIES INSTEAD OF SUPPORT WHEEL:

91,- 101 6110	Support wheel with angular gear
146,- 101 6120	Support winch mech. max. 1000 kg support weight

Standard equipment:

Chassis:	C-pressed section frame 5 mm, trailer coupling, towing facility (D/H: 40/31 mm)
Platform frame:	C-trapezoidal tipping frame
Platform:	Conical platform with 4 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion)
Sideboards:	Steel sideboards 400 mm with skirting board, cavity priming, sideboard hinges: 3 lateral and 2 rear, plugged corner stanchions, swing board rear, without slide
Tipping facility:	Ball tipping mountings with conical socket, 2-stage lifting cylinder 600 mm, hard-chromed, automatic stroke limitation
Brake installation:	Austria: Changing brake Germany: Parking brake
Support:	Support wheel, high-hinged and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity-primed sideboards, superstructure HB-green
Licence:	Austria: 25 km/h with type certificate agriculture Germany: true for traffic admission as non-braked trailer, dead weight of the tractor must be at least 2x axle load of the trailer

