

BRANTNER

SINGLE-AXLE THREE-SIDED TIPPER E 6535/E 6035

10 YEARS WARRANTY ON CHASSIS FRAME

**Perm. gross weight: A/G: approx. 6,5 to/6 to
Payload A/G: approx. 5 to/4 to
Platform size outside:
3500 x 1900 x 450 + 500 mm**

Technical data approx.:

Permissible gross weight	6500/6000 kg
Dead weight:	1460 kg
Platform size inside:	3430 x 1830 mm
Overall length:	A/G: 4930 / 5150 mm
Overall width:	2020 mm
Steel sideboard:	450 mm
Steel attachment board	500 mm
Track:	1470 mm
Axle cross section:	60 mm
Platform height:	970 mm
Tyres:	12.5/80 - 15.3 (14) with tube
Tipping cylinder stage	3
Stroke length:	1200 mm
Cylinder diameter:	approx. 60/75/90 mm
Max. operating pressure	200 bar
Tipping angle lateral/	approx. 45/45 °
Required amount of oil	approx. 6 l

Euro without

VAT	Art. Nr.	
6.624,-	105 0000	Basic price for E 6535 25 km/h version Austria with changing brake
7.036,-	105 0001	Basic price for E 6035 25 km/h version Germany with overrunning brake with moving automatism

196,- 105 0100 Germany vehicle certificate 25 km/h (for agriculture not required)

CHASSIS:

222,-	105 2300	steel base 5 mm
Series	105 1100	Trailer coupling 25 km/h
681,-	105 1210	Suspension of the axle

PLATFORM:

359,- 105 2015 Platform width 1,70; 1,75, 1,80 or 1,85 m

BODY:

o.MP	105 3236	Steel sideboards 400 mm instead of 450 mm
85,-	105 3244	Steel sideboards 500 mm instead of 450 mm
127,-	105 3240	Steel attachment boards 600 mm instead of 500 mm
265,-	105 3370	Collapsible attachment boards (Track 1330 mm) not for 15.0 / 55 - 17
139,-	105 3371	attachments collapsible with boards (not together)
743,-	105 3200	2 nd set steel attachment boards 400 mm *)
288,-	105 3110	Swing board left and right with central locking lever
236,-	105 3120	Sideboard lifting springs left and right
255,-	105 3430	Set skewing pillars with corner chains
131,-	105 3440	Set corner chains
79,-	105 3480	Grain slide lateral
61,-	105 3460	Discharge channel not lockable
142,-	105 3470	Discharge channel with additional fine dosing for grain slide
-777,-	105 3400	Price reduction: Delivery without swing attachments
Series	105 3100	Swing board rear
Series	105 3485	Grain slide rear
1.310,-	102 3730	Leave grating board 600 mm high

TIPPING INSTALLATION:

40,-	105 5110	Shut-off valve
293,-	105 5120	Hand operated pump combined with HD-connection

Standard equipment:

Chassis:	C-pressed section frame 5 mm, trailer coupling, towing facility: (D/H: 40/31 mm)
Platform:	Platform with 4 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 450 mm with skirting board 70 mm, cavity priming, sideboard hinges: 5 lateral and 4 rear, plugged corner stanchions, swing board rear with central locking lever, grain slide with lever
Swing attachments:	1 st set swing attachments 500 mm high with attachment corner stanchions
Tipping facility:	Ball tipping mounting with conical socket, 3-stage lifting cylinder, 1200 mm, hard-chromed, cardanic mounting, automatic stroke end limitation,
Brake installation:	Austria: Changing brake Germany: Overrunning brake with moving automatism
Support:	Support wheel, high-hinged and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity-primed sideboards, superstructure HB-green
Licence:	Austria: Type certificate 25 km/h agriculture 6,5 to PGW Germany: ABE 25 km/h agriculture 6 to PGW

Euro without

VAT Art. Nr.

TIPPING INSTALLATION:

410,- 105 5140 Rear hydraulic connection

BRAKING SYSTEMS:

1.189,-	105 5615	2-line airbrake instead of changing brake (only f. A)
720,-	105 5610	2-line airbrake system instead of overrunning moving automatism 25 km/h (only f. G)
1.154,-	105 5620	2-line airbrake additional f. overrunning moving automatism. (G)

QUICK RUNNER VERSIONS AUSTRIA

4.434,-	105 7100	40 km/h version: behind agriculture tractors: 2-line airbrake system, with ALB, with suspension, reinforced special axes, underride guard, mudguards, licence plate lighting, tyres 355/60 R 18 (16), contour lamps, white lamps front, gravel splash guard in the wheel area
---------	----------	--

QUICK RUNNER VERSIONS GERMANY

1.994,-	105 7101	40 km/h version: behind agriculture tractors: moving automatism brake, without airbrake, with suspension, reinforced 70 mm axes, wheel brake 300x80. underride guard, mudguards, licence plate lighting 355/60 R 18 (16), permissible gross weight 6000 kg, gravel splash guard in the wheel area, TÜV-acceptance
---------	----------	--

CAUTION: Required for non agriculture tractors:

424,-	105 7510	Contour and side marker lamps (not required in connection with agriculture tractors)
543,-	105 7520	AGS-automatic linkage adjuster for airbraked axes (not required in connection with agriculture tractors)

TYRES INSTEAD OF STANDARD TYRES:

-182,-	105 8120	Price reduction: 11.5/80 - 15.3 (10) with tube, only 6 to perm.gross weight
20,-	105 8130	13.0/75 - 16 (10) with tube
77,-	105 8150	15.0/55 - 17 (10) tbl.
274,-	105 8280	355/60 R 18 MPT (16) tbl.
434,-	105 8290	340/65 R 18 Michelin tbl.

SUPPORT FACILITIES INSTEAD OF SUPPORT WHEEL:

91,-	105 6110	Support wheel with angular gear
146,-	105 6120	Support winch mech. max. 1000 kg support weight