

# BRANTNER

## SINGLE-AXLE THREE-SIDED TIPPER E 7538

### 10 YEARS WARRANTY ON CHASSIS FRAME

**Permissible gross weight: approx. 7,5 to  
Payload: approx. 6 to  
Platform size outside:  
3800 x 2060 x 450 + 500 mm**

#### Technical data approx.:

Permissible gross weight:	7500 kg
Dead weight:	1560 kg
Platform size inside:	<b>3730 x 1990 mm</b>
Overall length:	5270 mm
Overall width:	2180 mm
Steel sideboards:	450 mm
Steel attachment board:	500 mm
Track:	1470 mm
Axle cross section:	70 mm
Platform height:	approx. 980 mm
Tyres:	355/60 R 18 (16) MPT tbl.
Tipping cylinder stage:	3
Stroke length:	1400 mm
Cylinder diameter:	approx. 75/90/105 mm
Max. operating pressure:	200 bar
Tipping angle lateral/	approx. 45/45 °
Required amount of oil:	approx. 8,5 l

#### Euro without

**VAT Art. Nr. 7.745,- 107 0000 Basic price for E 7538 25 km/h version Austria with changing brake**

**8.449,- 107 0001 Basic price for E 7538 25 km/h version Germany with overrunning brake and moving automatism**

**196,- 107 0100 Germany vehicle certificate 25 km/h (not required for agriculture)**

#### CHASSIS:

**146,- 107 2001 Platform wide 1900 mm - Type E 7538 S**

**Series 107 Trailer coupling 25 km/h**

**681,- 107 1210 Suspension of the axle**

#### BODY:

**220,- 107 2300 Steel wide 5 mm**

**287,- 107 3110 Swing board left + right with central locking lever**

**85,- 107 3244 Steel sideboards 500 mm instead of 450 mm**

**127,- 107 3240 Steel attachment boards 600 mm instead of 500 mm**

**979,- 107 3200 2<sup>nd</sup> set steel attachment boards 400 mm \*)**

**1.156,- 107 3210 2<sup>nd</sup> set steel attachment boards 500 mm \*)**

**1.323,- 107 3220 2<sup>nd</sup> set steel attachment boards 600 mm \*)**

**293,- 107 3230 3<sup>rd</sup> set steel attachment board 500 mm only rear**

**236,- 107 3120 Sideboard lifting springs left and right**

**265,- 107 3160 Collapsible attachment boards left and right**

**255,- 107 3430 Set skewing pillars with corner chains**

**131,- 107 3440 Set corner chains**

**41,- 107 3490 Potato slide (450 mm wide)**

**61,- 107 3460 Discharge channel not lockable**

**142,- 107 3470 Discharge channel with additional fine dosing for grain slide**

**249,- 107 3475 Discharge channel with additional fine dosing for potato slide**

**-777,- 107 3400 Price reduction: Supply without swing attachments**

**3.059,- 107 3510 Tarpaulin body with roll-up tarpaulin, consisting of: Attachment triangles 300 mm front and rear, fixed tarpaulin bar, tarpaulin rolled from right to left with aluminium slat and operating platform with railing at the face end, Hydraulic support foot required (no space to crank)**

#### Standard equipment

**Chassis:** V-frame made of C-pressed section frame 6 mm, trailer coupling, towing facility: (D/H: 40/31 mm)

**Platform frame:** V-trapezoidal tipping frame

**Platform:** Platform with **4 mm steel plate base** folded from one piece to all four side, no weld seam (foil seam fusion), patented self-cleaning platform edge

**Sideboards:** Steel sideboards 450 mm with skirting board 70 mm, cavity priming, sideboard hinges: 5 lateral and 4 rear, plugged corner stanchions, swing board rear with central locking lever, grain slide with lever

**Swing attachments:** 1<sup>st</sup> set steel swing attachments 500 mm high with attachment corner stanchions

**Tipping facility:** Ball tipping mounting with conical socket, 3-stage lifting cylinder, 1400 mm, hard-chromed, cardanic mounting, automatic stroke end limitation

**Brake installation:** Austria: Changing brake  
Germany: Overrunning brake with moving automatism

**Support:** Support wheel, high-hinged and adjustable in height

**Electricity:** 12 voltage light and indicator system, socket rear

**Paintwork:** Dip priming and 2 component acrylic paint hot spray painting cavity-primed sideboard, superstructure HB-green

**Licence:** Austria: type certificate 25 km/h agriculture  
Germany: ABE 25 km/h agriculture 7,5 to PGW

#### Euro without

**VAT Art. Nr.**

#### TIPPING INSTALLATION:

**40,- 107 5110 Shut-off valve**

**4.092,- 107 5160 High tipping installation (approx. 750 mm higher)**

**293,- 107 5120 Hand operated pump combined with HD-connection**

**410,- 107 5200 Rear hydraulic connection**

**145,- 107 5210 Lifting cylinder 60/75/90/105 - 1600 mm, oil quantity approx. 9 l, tipping angle approx. °45/50**

#### BRAKING SYSTEMS:

**1.189,- 107 5615 2-line airbrake instead of changing brake (only f. A)**

**777,- 107 5610 2-line airbrake system instead of overrunning moving automatism 25 km/h (only for Germany)**

**1.246,- 107 5620 2-line airbrake additional overrunning moving automatism (G)**

**562,- 107 5760 Hydraulic brake without load adaptation valve (only for Austria) 10 km/h**

**1.037,- 107 5765 Hydraulic brake with load adaptation (only for Austria) 10 km/h**

#### QUICK RUNNER VERSIONS AUSTRIA

**4.530,- 107 7100 40 km/h version:** behind agriculture tractors: 2-line airbrake system, with ALB, with suspension, reinforced special axes, underdrive guard, mudguards, licence plate lighting, tyres 385/65 R 22.5 remould 80 km/h, contour lamps, white lamps front, gravel splash guard in the wheel area

#### QUICK RUNNER VERSIONS GERMANY

**3.718,- 107 7101 40 km/h version:** behind agriculture tractors: 2-line brake, with suspension, reinforced special axes, underdrive guard, mudguards, licence plate lighting, tyres 385/65 R 22.5 remould 80 km/h, gravel splash guard in the wheel area

**CAUTION:** Required for non agriculture tractors:

**424,- 107 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)**

**543,- 107 7520 AGS- autom. linkage adjuster for airbraked axes (not required in connection with agriculture tractors)**

#### TYRES INSTEAD OF STANDARD TYRES

**156,- 107 8290 340/65 R 18 Michelin tbl**

#### SUPPORT FACILITIES INSTEAD OF SUPPORT WHEEL

**91,- 107 6110 Support wheel with angular gear**

**323,- 107 6140 Semi trailer support winch with 2 speeds**