

# BRANTNER SINGLE-AXLE THREE-SIDED TIPPER **E 10.041**

## 10 YEARS WARRANTY ON CHASSIS FRAME

**Permissible gross weight: 10 to, Payload 7,5**  
**Platform size outside**  
**4140 x 2150 x 600 + 600 mm**  
**25 km/h 2-line airbrake**

### Technical data approx.:

Permissible gross weight:	10000 kg
Dead weight:	2300 kg
Platform size inside:	<b>4070 x 2080 mm</b>
Overall length:	5.410 mm
Overall width:	2300 mm
Steel sideboards:	600 mm
Attachment boards:	600 mm
Track:	1600 mm
Axle cross section:	90 mm
Platform height:	approx. 1180 mm
Tyres:	385/65 R 22,5 remould 80 km/h
Tipping cylinders stage:	3
Stroke length:	1400 mm
Cylinder diameter:	75 / 90 / 105 mm
Max. operating pressure:	200 bar
Tipping angle lateral/	45/45 degrees
Required amount of oil:	8,5 l

### Euro without

VAT Art. Nr.

**12.255,-** 110 0000 **Basic price for E 10.041 with 2-airbrake system**

#### **CHASSIS:**

**681,-** 110 1210 Suspension of the axes

#### **PLATFORM:**

**788,-** 110 2010 Plateau width 1,80; 1,90; or 2,00 m

#### **BODY:**

**287,-** 110 3110 Swing board left and right with central locking system

**979,-** 110 3200 2<sup>nd</sup> set steel attachment boards 400 mm \*)

**1.156,-** 110 3210 2<sup>nd</sup> set steel attachment boards 500 mm \*)

**1.323,-** 110 3220 2<sup>nd</sup> set steel attachment boards 600 mm \*)

**293,-** 110 3230 3<sup>rd</sup> steel attachment board 500 mm only rear

**236,-** 110 3120 Sideboard lifting springs left + right

**300,-** 110 3160 Collapsible attachment boards le + ri (Plateau 2220

**71,-** 110 3450 Tension chains (1 set per set boards)

**255,-** 110 3430 Set skewing pillars with corner chains

**131,-** 110 3440 Set corner chains

**41,-** 110 3490 Potato slide (450 mm wide)

**61,-** 110 3460 Discharge channel not lockable

**142,-** 110 3470 Discharge channel + add. fine dosing for grain slide

**249,-** 110 3475 Discharge channel with additional fine dosing for potato slide

**317,-** 110 3500 Attachment triangles 300 mm high front and rear

**293,-** 110 3520 Hydraulic lateral swing sideboard plug-type unlocking left and right

**370,-** 110 3525 (upon subsequent delivery)

**-920,-** 110 3400 Price reduction: Supply without swing attachments

**3.059,-** 110 3510 Tarpaulin body with roll-up tarpaulin, consisting of: Attachment triangles 300 mm front and rear, fixed tarpaulin bar, tarpaulin rolled from right to left with aluminium slat and operating platform with railing at the face end, Hydraulic support foot required (no space to crank)

#### **SILAGE BODIES:**

**3.733,-** 110 4136 Silage body with hydr. rear wall (with double-acting cylinders) **1800 mm** high, **grain tight, including 2<sup>nd</sup>** swing attachment, approx. 18 m<sup>3</sup>, rear wall made of 4 mm steel plate with grain slide, with plug-type rear hydraulic connection, view grille (perforated sheet), 4-stage lifting cylinder 1600 mm lift,

### Standard equipment:

Chassis: V-frame made of C-pressed section frame 8 mm, trailer coupling (in Austria at single approving only for using inside factory), towing facility: (D/H: 40/31 mm)

Platform frame V-trapezoidal tipping frame

Platform: Platform with **5 mm steel plate base folded** from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge

Sideboards: Steel sideboards: 600 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 5 lateral and 4 rear, plugged corner stanchions, swing board rear, grain slide with adjusting lever

Swing attachments: 1<sup>st</sup> set steel attachment boards 600 mm high, with attachment corner stanchions

Tipping facility: Ball tipping mounting with conical socket, 3-stage lifting cylinder 1400 mm, hard-chromed, cardanic mounting, automatic stroke limitation

Brake installation: 2-line airbrake system

Support: Support wheel, high-hinged and adjustable in height

Electricity: 12 voltage light and indicator system

Paintwork: Dip priming and 2 component acrylic paint hot spray painting, cavity primed sideboards, superstructure HB-green

Licence: Austria: Type certificate 25 km/h agriculture  
Germany: Operating permit 25 km/h agriculture

### Euro without

VAT Art. Nr.

#### **SILAGE BODIES:**

**359,-** 110 3230 Additional lower rear board with grain slide and corner stanchions for 600 mm height incl. closures

**309,-** 110 3235 Additional 1<sup>st</sup> attachment board 600 mm rear with corner stanchions and closures

#### **TIPPING INSTALLATION:**

**40,-** 110 5110 Shut-off valve

**4.092,-** 110 5160 High tipping installation (approx. 750 mm higher) with own connection

**293,-** 110 5120 Hand operated pump combined with HD-connection

**410,-** 110 5200 Rear hydraulic connection

**145,-** 110 5210 Lifting cylinder 60 / 75 / 90 / 105 - 1600 mm  
Oil quantity approx. 9 l, tipping angle approx. 45/49 °

#### **SUPPORT FACILITIES INSTEAD OF SUPPORT WHEEL:**

**91,-** 110 6110 Support wheel with angular gear

**145,-** 110 6120 Support winch max. 1000 kg support weight

**323,-** 110 6140 Semi trailer support winch with 2 speeds

**448,-** 110 6130 Hydraulic support foot with protected double-acting (pipe in pipe guide) + locking block as standards

#### **QUICK RUNNER VERSIONS AUSTRIA**

**2.343,-** 110 7100 **40 km/h version:** behind agriculture tractors, 2-line airbrake system, with ALB, with suspension, reinforced special axes, underride guard, mudguards, licence plate lighting, tyres 385/65 R 22,5 remould, contour lamps; white lamps front, gravel splash guard in the wheel area

#### **QUICK RUNNER VERSIONS GERMANY**

**1.515,-** 110 7101 **40 km/h version** behind agriculture tractors, 2-line airbrake system, **spring born**, reinforced axes, underride guard, mudguards, licence plate lighting, tyres 385/65 R 22,5 remould, gravel splash guard in the wheel area

**CAUTION:** Required for non agriculture tractors:

**424,-** 110 7510 Contour lamps and side marker lamps

**543,-** 110 7520 AGS - automatic linkage adjuster for airbraked axle