

BRANTNER TANDEM THREE-SIDED TIPPER TA 8438

10 YEARS WARRANTY ON CHASSIS FRAME

Perm. gross weight: 8,4 t, Payload ca. 6,5 t
Platform size outside:
3800 x 2060 x 450 + 500 mm
25 km/h

Technical data approx.:

Permissible gross weight	8400 kg
	from 1.10.2006 without DL installation max 8000 kg permissible gross weight
Dead weight:	1900 kg
Platform size inside:	3730 x 1990 mm
Overall length:	5270 mm
Overall width:	2180 mm
Steel sideboards:	450 mm
Attachment boards:	500 mm
Track:	1470 mm
Axle cross section:	60 mm
Platform height:	1030 mm
Tyres:	11.5/80 - 15.3 (10) with tube
Tipping cylinder stag	3
Stroke length:	1400 mm
Cylinder diameter:	75 / 90 / 105 mm
Max. operating pressure	200 bar
Tipping angle lateral/	45/45 degrees
Required amount of oil	8,5 l

Euro without

VAT Art. Nr.

10.422,- 201 0000 **Basic price TA 8438 version Austria with changing brake**

11.949,- 201 0001 **Basic price TA 8438 version Germany with Two-line-airbrake system**

Special equipment against extra charge

CHASSIS:

Series 201 1110	Trailer coupling 25 km/h - 8 t gross weight
206,- 201 1115	Trailer coupling over 25 km/h - 8 t gross weight
1.064,- 201 1130	Automatic trailer coupling incl. changed rear transverse girder

BODY:

85,- 201 3244	Steel sideboards 500 mm instead of 450 mm
150,- 201 3340	Steel attachment boards 600 mm instead of 500 mm
979,- 201 3200	2 nd set steel attachment boards 400 mm *)
1.156,- 201 3210	2 nd set steel attachment boards 500 mm *)
1.323,- 201 3220	2 nd set steel attachment boards 600 mm *)
293,- 201 3230	3 rd steel attachment board 500 mm only rear
121,- 201 3120	Sideboard lifting springs left and right
265,- 201 3160	Collapsible attachment boards left + right
71,- 201 3450	Tension chains 1 set per set walls
419,- 201 3430	Set skewing pillars with corner chains
131,- 201 3440	Set corner chains
41,- 201 3490	Potato slide (450 mm wide)
78,- 201 3596	View grille (perforated sheet) over the overall width instead of front attachment board
136,- 201 3598	View grille (perforated sheet) between stanchions with sheet metal cover
61,- 201 3460	Discharge channel not lockable
	Discharge channel with additional fine dosing
142,- 201 3470	for grain slide:
249,- 201 3475	for potato slide:
317,- 201 3500	Attachment triangles 300 mm high front and rear

Standard equipment:

Chassis:	V-frame made of C-pressed sections 6 mm, trailer coupling, tandem axle with leaf spring, control arm compensation and spring support, towing facility (D/H: 40/31mm)
Platform frame:	V-trapezoidal tipping frame
Platform:	Platform with 4 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge.
Sideboards:	Steel sideboards 450 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 5 lateral and 4 rear, plugged corner stanchions, pivot board rear, with central locking lever, grain slide with adjusting lever
Swing attachments:	1 st set steel attachment boards 500 mm high with attachment corner stanchions
Tipping facility:	Ball tipping mountings with conical socket, 3-stage lifting cylinders, 1400 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling, automatic stroke limitation
Brake installation:	Austria: Changing brake Germany: Two-line airbrake system
Support:	Support wheel high-hinged and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming with 2 component acrylic paint hot spray painting cavity-primed sideboards, superstructure HB green
Licence:	Austria: 25 km/h type certificate for agriculture Germany: 25 km/h BE agriculture PGW 8,4 to

Euro without

VAT Art. Nr.

BODY:

3.059,- 201 3510 **Tarpaulin body with roll-up tarpaulin**, consisting of: Attachment triangles 300 mm front and rear, fixed tarpaulin bar, tarpaulin can be rolled from right to left with aluminium slat and operating platform with railing at the face end, hydraulic support foot required no space to crank)

293,- 201 3520 Hydraulic lateral swing sideboard plug-type unlocking left and right

370,- 201 3525 Upon subsequent delivery

-777,- 201 3400 Price reduction: Supply without swing attachments

SILAGE BODIES:

3.986,- 201 4120 Silage body with hydraulic rear wall 1500 mm high, grain-tight, (with double-acting cylinders) incl. 2. swing attachments, approx. 12 m³ case volume, rear wall made of 4 mm steel plate with grain slide, with plug-type rear hydraulic connection, **view grille** (perforated sheet) **4-stage lifting cylinder 1600 mm,**

342,- 201 3234 Additional lower rear board with grain slide and corner stanchions, height 500 mm with closures

293,- 201 3235 Additional 1st attachment board 500 mm rear with corner stanchions and closures

309,- 201 3237 Additional 1st attachment board 600 mm rear with corner stanchions and closures

TIPPING FACILITY

Series 201 5110 Shut-off valve

4.092,- 201 5160 High tipping facility (approx. 750 higher, additional oil quantity required approx. 8 l) with own connection

410,- 201 5200 Rear hydraulic connection

145,- 201 5210 Lifting cylinder 60/75/90/105 - 1600 mm, oil quantity approx. 9 l, Tipping angle approx. ° 45/50

Euro without
VAT Art. Nr.

BRAKING SYSTEMS:

- Series 201 5602 Both axes braked
- 1.526,-** 201 5615 Two-line airbrake system instead of changing brake (only for Austria)
- 359,-** 201 5710 Rear connection with two-line airbrake system
- 398,-** 201 5750 ALB (automatic load-dependent brake force control) of the 2-line air brake system, if not included in quick runner packet
- 726,-** 201 5760 Hydraulic brake without load adaptation valve instead of changing brake (10 km/h)
- 1.236,-** 201 5765 Hydraulic brake with load adaptation valve instead of changing brake (10 km/h)

QUICK RUNNER VERSIONS AUSTRIA

- 3.441,-** 201 7100 **40 km/h-version** behind agriculture tractors:
2-line air brake system with **ALB**, axes with EG-brake test, underride guard, mudguards, licence plate lighting, tyres 11.5/80 - 15.3 (10) with tube, contour lamps, white lamps front, gravel splash guard in the wheel area

QUICK RUNNER VERSIONS GERMANY

- 922,-** 201 7101 **40 km/h-version** behind agriculture tractors:
2-line air brake system working onto all 4 wheels, without ALB, without ABS, axes with EG-brake test, underride guard, mudguards, quick runner lighting system, tyres: 11.5/80 - 15.3 (10) with tube, gravel splash guard in the wheel area

CAUTION: Required for non agriculture tractors:

- 424,-** 201 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)
- 1.088,-** 201 7520 AGS - automatic linkage adjusters for air braked axles (not required in connection with agriculture tractors)

TYRES INSTEAD OF STANDARD TYRES

- 363,-** 201 8125 12.5/80 - 15.3 (14) with tube
- 404,-** 201 8130 13.0/75 - 16 (10) with tube
- 512,-** 201 8150 15.0/55 - 17 (10) tbl.
- 1.507,-** 201 8160 19.0/45 - 17 (10) tbl.
- 880,-** 201 8270 275/65 R 18 Michelin tbl.
- 911,-** 201 8280 355/60 R 18 MPT (16) tbl.
- 1.227,-** 201 8290 340/65 R 18 Mich. Steel case tbl.

SUPPORT FACILITIES:

- 91,-** 201 6110 Support wheel with angular gear
- 145,-** 201 6120 Trailer support mechanical max. 1000 kg support
- 323,-** 201 6140 Semi trailer support winch with 2 speeds
- 448,-** 201 6130 Hydr. support foot with protected double-acting cyl. (pipe in pipe guide, with locking block as standards)
- 761,-** 201 6150 Hydr. support "sloped" with protected single-acting cylinder (cylinder can not be damaged at coupling, only required single-acting controlling apparatus)

