

BRANTNER TANDEM THREE-SIDED TIPPER TA 8040

10 YEARS WARRANTY ON CHASSIS FRAME

**Perm. gross weight: 8, Payload ca. 6 to
Platform size outside
4050 x 2060/2150 x 500 + 500 mm
Swing board left, right, rear**

Technical data approx.:

Perm. gross weight:	8000 kg
Dead weight:	2050 kg
Platform size inside:	3980 x 1990/2080 mm
Overall length:	5750 mm
Overall width:	2250 mm
Steel sideboards:	500 mm
Attachment boards:	500 mm
Track:	1600 mm
Spring distance:	1000 mm
Axle cross section:	65 mm
Platform height:	1170 mm
Tyres:	11.5/80 - 15.3 (10) with tube
Tipping cylinder stage	3
Stroke length:	1400 mm
Cylinder diameter:	75 / 90 / 105 mm
Max. operating pressure	200 bar
Tipping angle lateral/r	45/45 degrees
Required amount of oil	8,5 l

EURO without

VAT	Art. Nr.	
11.601,-	202 0000	Basic price TA 8040; overrunning brake with moving automatism
196,-		Germany: Vehicle certificate 25 km/h (for agriculture not required) net

Special equipment against extra charge

CHASSIS:

series 202	1110	Trailer coupling 25 km/h - 8 to gross weight
206,-	202 1115	Trailer coupling over 25 km/h - 8 to gross weight
1.064,-	202 1130	Automatic trailer coupling including changed rear cross girder

PLATFORM:

Series 202 2170 Conical platform

BODY:

979,-	202 3200	2 nd set steel attachment boards 400 mm *)
1.156,-	202 3210	2 nd set steel attachment boards 500 mm *)
1.323,-	202 3220	2 nd set steel attachment boards 600 mm *)
293,-	202 3230	3 rd steel attachment board 500 mm only rear
121,-	202 3120	Sideboard lifting springs left + right
71,-	202 3450	Tension chains 1 set per set walls
419,-	202 3430	Set skewing pillars with corner chains
131,-	202 3440	Set corner chains
41,-	202 3490	Potato slide (450 mm wide)
78,-	202 3596	View grille (perforated sheet) over the overall width instead of front attachment board
136,-	202 3598	View grille (perforated sheet) between stanchions with sheet metal cover
61,-	202 3460	Discharge channel not lockable
		Discharge channel with additional fine dosing:
142,-	202 3470	for grain slide
249,-	202 3475	for potato slide
317,-	202 3500	Attachment triangles 300 mm high front and rear

Standard equipment:

Chassis:	Frame made of closed C-pressed sections 6 mm, with stable underride guard, trailer coupling, tandem axle with leaf spring, control arm compensation and spring support, towing facility: (D/H: 40/31mm)
Platform frame:	V-trapezoidal tipping frame
Platform:	Conical platform with 5 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 500 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 5 lateral and 4 rear, plugged corner stanchions, swing board left/right and rear, with central locking lever and closing hook for 30 mm latching range, grain slide with adjusting lever
Swing attachments:	1 st set steel attachment boards 500 mm high, with attachment corner stanchions
Tipping facility:	Ball tipping mountings with conical socket, 3-stage lifting cylinder, 1400 mm, hard-chromed, cardanic mounting connection line with plug-in coupling and shut-off valve, automatic stroke limitation
Braking installation:	Overrunning brake with moving automatism, fourwheel braked
Support:	Support wheel, collapsible and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork	Dip priming and 2 component acrylic paint hot spray painting cavity-primed sideboards, superstructure HB-green
Licence:	Austria: Without type certificate - 10 km/h Germany: 25 km/h ABE agriculture

Euro without

VAT	Art. Nr.	
		BODY:
3.059,-	202 3510	Tarpaulin body with roll-up tarpaulin , consisting of: Attachment triangles 300 mm front and rear, fixed tarpaulin bar, tarpaulin rolled from right to left with aluminium slat and operating platform with railing at the face end, hydraulic support foot required (no space to crank)

293,-	202 3520	Hydraulic lateral swing sideboard plug-type unlocking left and right
370,-	202 3525	Upon subsequent delivery
-931,-	202 3400	Supply without swing attachments

SILAGE BODIES:

3.986,-	202 4120	Silage body with hydraulic rear wall 1,500 mm high, grain tight, (with double-acting cylinder) incl. 2 nd swing attachment approx 12 m ³ case volume, rear wall made of 4 mm steel plate with grain slide and plug-type rear hydraulic connection, view grille (perforated sheet), 4-stage lifting cylinder 1600 mm
342,-	202 3234	Additional lower rear board with grain slide and corner stanchions for 500 mm height + closures
293,-	202 3235	Additional 1 st attachment board 500 mm rear with corner stanchions and closures
309,-	202 3237	Additional 1 st attachment board 600 mm rear with corner stanchions and closures

TIPPING FACILITY:

Series 202	5110	Shut-off valve
4.091,-	202 5160	High tipping installation (approx. 750 mm higher, additional oil quantity required approx. 8 l) with own connection
410,-	202 5200	Rear hydraulic connection
145,-	202 5210	Lifting cylinder 60/75/90/105 - 1600 mm, oil quantity approx 9 l, tipping angle approx ° 45/50

EURO without
VAT Art. Nr.

BRAKING SYSTEMS:

Series 202	5602	Both axes braked
1.116,-	202 5610	2-line airbrake system instead of overrunning moving automatism brake for 25 km/h
1.526,-	202 5620	2-line airbrake instead of changing brake add. to overrunning moving automatism brake for 25 km/h
359,-	202 5710	Rear connection with two-line airbrake system
398,-	202 5750	ALB (automatic load-dependent brake force control) of the 2-line airbrake system (if not included in quick runner packet)

QUICK RUNNER VERSIONS AUSTRIA

2.124,-	202 7120	40 km/h-version behind agriculture tractors: 2-line airbrake system with ALB , axes with EG-brake test, underride guard, mudguards, licence plate lighting, tyres 11.5/80 - 15.3 (10) with tube, contour lamps, white lamps front, gravel splash guard in the wheel area
5.972,-	202 7210	60 km/h-version behind agriculture tractors: 2-line airbrake with ALB , with ABS , axes with EG-brake test, underride guard, mudguards, contour lamps, white lamps front 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area
6.275,-	202 7311	80 km/h-version behind agriculture tractors: 2-line airbrake working onto all four wheels, with ALB , with ABS , 7-pole, 24 voltage , axes with EG-brake test, with automatic linkage adjuster, underride guard, mudguards, contour lamps, fog tail lamp, white lamps front, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

QUICK RUNNER VERSIONS GERMANY

620,-	202 7103	40 km/h-version: behind agriculture tractors: moving automatism brake working onto all four wheels, without airbrake, mudguards on the rear wheels, quick runner lighting system, 7-pole, 12 voltage, tyres 11.5/80 - 15.3 (10) with tube, gravel splash guard in the wheel area
1.298,-	202 7101	40 km/h-version: behind agriculture tractors: 2-line airbrake system working onto all four wheels, without ALB, without ABS, axes with brake 300 x 80, underride guard, mudguards on the rear wheels, quick runner lighting system, 7-pole, 12 voltage, tyres 11.5/80 - 15.3 (10) with tube, gravel splash guard in the wheel area
2.372,-	202 7201	60 km/h-version: behind agriculture tractors: 2-line airbrake system working onto all four wheels, without ALB, without ABS, axes with brake 300 x 80, underride guard, mudguards on the rear wheels, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area
5.959,-	202 7301	80 km/h-version behind agriculture tractors: 2-line airbrake system working onto all four wheels with ALB, with ABS, 7-pole, 24 voltage, axes with brake 300 x 80, with automatic linkage adjuster, underride guard, mudguards on the rear wheels, fog tail lamps, quick runner lighting system, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

CAUTION: Required for non agriculture tractors

424,-	201 7510	Contour lamps and side marker lamps (not required in connection with agriculture tractors)
1.088,-	201 7520	AGS - automatic linkage adjuster for airbraked axes (not required in connection with agriculture tractors)

EURO without
VAT Art. Nr.

TYRES INSTEAD OF STANDARD TYRES:

363,-	202 8125	12.5/80 - 15.3 (14) with tube
404,-	202 8130	13.0/75 - 16 (10) with tube
512,-	202 8150	15.0/55 - 17 (10) tbl.
1.507,-	202 8160	19.0/45 - 17 (10) tbl.
880,-	202 8270	275/65 R 18 Michelin tbl.
911,-	202 8280	355/60 R 18 MPT (16) tbl.
1.227,-	202 8290	340/65 R 18 (16) Mich. Steel case tbl.
510,-	202 8900	Spare wheel mounting at the forehead wall

SUPPORT FACILITIES:

91,-	201 6110	Support wheel with angular gear
145,-	201 6120	Support winch mech. max. 1000 kg support weight
323,-	202 6140	Semi trailer support winch with 2 speeds
448,-	202 6130	Hydraulic support foot with protected double-acting cylinder (pipe in pipe guide, serial with locking block)

