

BRANTNER TA 8045 XXL

TANDEM THREE-SIDED TIPPER

10 YEARS WARRANTY ON CHASSIS FRAME

Permissible gross weight: 8 t, PL approx. 5,5 t
Platform size outside
4550 x 2220/2320 x 500 + 500 mm
Swing board left + right + rear

Technical data approx.:

Perm. gross weight:	8000 kg
Dead weight:	2580 kg
Platform size inside :	4480 x 2150/2250 mm
Overall length:	6320 mm
Overall width:	2420 mm
Steel sideboards:	500 mm
Attachment boards:	500 mm
Track:	1800 mm
Spring distance:	1220 mm
Axle cross section:	70 mm
Platform height:	1140 mm
Tyres:	13.0/75 - 16 (10) with tube
Tipping cylinder stage	4
Stroke length:	1800
Cyl. diameter with 2 c	60/75/90/105
Max. operating pressure	200 bar
Tipping angle lateral/i	45/49 Degrees
Required amount of c	10,5 / 21 l

Euro without

VAT Art. Nr.

12.731,- 203 0000 **Basic price w. 1 lifting cyl. TA 8045 XXL w. overrunning brake + moving automatism**

13.401,- 203 0001 **Basic price with 2 lifting cyl. TA 8045 XXL + overrunning brake + moving automatism**

196,- Germany: Vehicle certificate 25 km/h (for agriculture not required) net

Special equipment against extra charge

CHASSIS

Series 203 1110	Trailer coupling 25 km/h - 8 t gross weight
206,- 203 1120	Trailer coupling over 25 km/h - 8 t gross weight
239,- 203 1116	Track 1920 mm, axle cross section 80 mm, axle load 7,0 t./axle (9000 kg under 1 axle) with 25 km/h
198,- 203 1190	Gravel splash guard in the wheel area

CHASSIS:

168,- 203 3240	Steel sideboards 600 mm instead of 500 mm
136,- 203 3340	Steel swing attachment boards 600 instead 500 mm
979,- 203 3200	2 nd set steel attachment boards 400 mm *)
1.156,- 203 3210	2 nd set steel attachment boards 500 mm *)
1.323,- 203 3220	2 nd set steel attachment boards 600 mm *)
293,- 203 3230	3 rd steel attachment boards 500 mm only rear
309,- 203 3420	Steel sideboards 2,5 mm instead of 2 mm per set
121,- 203 3120	Sideboard lifting springs left + right
71,- 203 3450	Tension chains (1 set per set walls)
419,- 203 3430	Set skewing pillars with corner chains
131,- 203 3440	Set corner chains
90,- 203 3480	Additional grain slide/piece
41,- 203 3490	Potato slide (450 mm wide)
78,- 203 3596	View grille (perforated sheet) over the overall width instead of front attachment board
136,- 203 3598	View grille (perforated sheet) between stanchions with sheet metal cover
61,- 203 3460	Discharge channel not lockable
	Discharge channel with additional fine dosing
142,- 203 3470	for grain slide:
249,- 203 3475	for potato slide:

Standard equipment:

Chassis:	Frame made of very stable G-pressed sections 225 x 100, 8 mm thick, with stable underide guard, cross stiffening, trailer coupling (in Austria at single approving only for using inside factory), 40 km/h tandem axle with leaf spring, control arm compensation and spring support, towing facility: (D/H: V-trapezoidal tipping frame
Platform frame:	V-trapezoidal tipping frame
Platform:	Conical platform with 5 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 500 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 6 lateral and 4 rear, plugged corner stanchions, pivot board left/right and rear, with central locking lever and closing hook for 30 mm latching range, large closures, grain slide with adjusting lever
Swing attachments:	1 st set steel swing attachments 500 mm high, with attachment corner stanchions
Tipping facility:	Ball tipping mountings with conical socket, 3/4-stage lifting cylinder, 1600 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling and shut-off valve, automatic stroke limitation
Braking installation:	Overrunning brake with moving automat., fourwheel braked
Support:	Support wheel, collapsible and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity-primed sideboards, superstructure HB green
Licence:	Austria: Without type certificate - 10 km/h Germany: 25 km/h ABE agriculture

Euro without

VAT Art. Nr.

BODY:

317,- 203 3500	Attachment triangles 300 mm high front and rear
1.960,- 203 3515	Tarpaulin body with roll-up tarpaulin , consisting of: Attachment triangles 300 mm front + rear, folding-type tarpaulin bar, tarpaulin can rolled from right to left + aluminium slat and operating platform + railing at the face end (f. serial platform)
2.114,- 203 3511	Tarpaulin body with roll-up tarpaulin as above only: tarpaulin rolled from left - right (access ladder right)
293,- 203 3520	Hydraulic lateral swing sideboard plug-type unlocking left and right
370,- 203 3525	Upon subsequent delivery
1.023,- 203 3530	Hydraulic swing sideboard unlocking rear
3.214,- 203 3540	Hydraulic lateral 180° sideboard opening and closing (additional double-acting control unit required on tractor)
415,- 203 3570	Stable chute lateral approx 360 mm high per side, for opening jointly with lateral swing sideboard unlocking (only with track 1800 mm possible)
250,- 203 3410	Sideboard stiffening left and right per set
-931,- 203 3400	Price reduction: Supply without swing attachments

TIPPING INSTALLATION

Series 203 5110	Shut-off valve
203 5310	Lifting cylinder 60/75/90/105 - 1800 mm, oil quantity per cylinder approx. 10,5 l, tipping angle approx ° 45/49
Series 203 5310	with 1 cylinder
Series 203 5311	with 2 cylinders
4.091,- 203 5160	High tipping installation (approx. 750 mm higher, additional required oil amount approx. 8 l) with own connection
293,- 203 5120	Hand-operated pump combined with hydraulic connection for tipper with 1 tipping cylinder
410,- 203 5200	Rear hydraulic connection

Euro without
VAT Art. Nr.

SILAGE BODIES:

3.397,- 203 4120 Silage body with hydraulic rear wall 1500 mm, grain tight, (with double-acting cylinders), including 2nd swing attachment 500 mm with grain slide approx 15 m³, rear wall made of 4 mm steel plate, with plug-type rear hydraulic connection, **view grille** (perforated sheet), **4-stage lifting cylinder 1800 mm**

3.998,- 203 4136 Silage body with hydraulic rear wall 1800 mm, grain tight, (with double-acting cylinders), including 2nd swing attachment (600 mm), approx. 18 m³, rear wall made of 4 mm steel plate, as well as rise of sideboard and attachment board from 500 to 600 mm, with grain slide, with plug-type rear hydraulic connection, **view grille** (perforated sheet), **4-stage lifting cylinder 1800 mm**

342,- 203 3234 Additional lower rear board with grain slide and corner stanchions 500 mm height with closures

298,- 203 3235 Additional 1st attachment board 500 mm rear with corner stanchions and closures

368,- 203 3238 Additional lower rear board with grain slide and corner stanchions, 600 mm height with closures

314,- 203 3237 Additional 1st attachment board 600 mm rear + corner stanchions + closures

203 3512 Tarpaulin body with roll-up tarpaulin in combination with hydraulic rear wall
LOOK AT PAGE 45

164,- 203 3513 Supports for hydraulic rear wall (supports left and right to support the hydraulic rear wall with uppermost attachment wall folded down)

BRAKING SYSTEMS:

Series 203 5602 Both axes braked

762,- 203 5610 Two-line airbrake system instead of overrunning moving automatism brake for 25 km/h

1.526,- 203 5620 Two-line airbrake system additional to overrunning moving automatism brake for 25 km/h

o. MP 203 5630 1-line airbrake system instead of 2-line airbrake system (only 25 km/h permitted)

208,- 203 5640 Combined one and two-line air brake system instead of two-line air brake system (only permitted 25 km/h)

359,- 202 5710 Rear connection with two-line air brake system

280,- 203 5730 Rear connection with 1-line air brake system

426,- 203 5740 Rear connection with 1 & 2-line air brake system

398,- 202 5750 ALB (automatic load-dependent brake force control) of the 2-line air brake system (if not included in quick runner packet)

QUICK RUNNER VERSIONS AUSTRIA

2.471,- 203 7100 **40 km/h-version** behind agriculture tractors: 2-line airbrake system with **ALB, without ABS**, 70 mm axes, underride guard, mudguards, quick runner lighting system, 7-pole, 12 V, tyres 13.0/75-16 (10)+ tube, contour- and side marker lamps, white lamps front, gravel splash guard in the wheel area

6.246,- 203 7300 **80 km/h-version** behind agriculture tractors: 2-line airbrake system with **ALB, with automatic linkage adjuster, with ABS**, 70 mm axes, underride guard, mudguards, 7-pole, 24 voltage, fog tail light, quick runner lighting system, tyres 355/60 R 18 MPT (16) tbl., contour- and side marker lamps, white lamps front, gravel splash guard in the wheel area

Euro without
VAT Art. Nr.

QUICK RUNNER VERSIONS GERMANY

328,- 203 7103 **40 km/h-version:** behind agriculture tractors: moving automatism working onto all 4 wheels, without airbrake, axes 70 mm, 300 x 60 / 6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 13.0/75 - 16 (10) with tube, gravel splash guard in the wheel area

1.416,- 203 7101 **40 km/h-version:** behind agriculture tractors: 2-line airbrake system, with ALB, without ABS, 70 mm axes 300 x 80 / 6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 13.0/75 - 16 (10) with tube, gravel splash guard in the wheel area

1.876,- 203 7105 **40 km/h-version:** behind agriculture tractors: moving automatism and 2-line airbrake combined, 70 mm axes, 300 x 60 / 6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 13.0/75 - 16 (10) with tube, gravel splash guard in the wheel area

1.904,- 203 7201 **60 km/h-version** behind agriculture tractors: 2-line airbrake system, 70 mm axes, 300 x 80 / 6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

5.918,- 203 7301 **80 km/h-version:** behind agriculture tractors: 2-line airbrake system with ALB, with ABS, 70 mm axes 300 x 80 / 6 with automatic linkage adjuster, underride guard, mudguards, fog tail light, quick runner lighting system, 7-pole, 24 voltage, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

CAUTION: Required for non agriculture tractors

424,- 203 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)

878,- 203 7520 AGS - automatic linkage adjuster for airbraked axes (not required in connection with agriculture tractors)

TYRES INSTEAD OF STANDARD TYRES:

113,- 203 8150 15.0/55 - 17 (10) tbl.

509,- 203 8280 355/60 R 18 MPT (16) tbl.

830,- 203 8290 340/65 R 18 (16) Mich. Steel case tbl.

-400,- 203 8120 Price reduction: 11.5/80 - 15.3 (10) with tube

none-retrofit tyres

1.233,- 203 8160 19.0/45 - 17 (10) tbl., track 1920 mm, axle cross section 80 mm, axle load 7000 kg/axle (9000 kg under tipper with one-axle) with 25 km/h

1.595,- 203 8170 500/50 - 17 (10) with tube, suitable up to 40 km/h, track 1920 mm, axle cross section 80 mm, axle load 7000 kg/axle (9000 kg under tipper with one axle) with 25 km/h

1.352,- 203 8182 505/50 R 17 MPT tbl., with doublehump security rim (corresponds 16 pr), suitable until 90 km/h, track 1920 mm, axle cross section 80 mm, axle load 7000 kg/axle (9000 kg under tipper with one axle) with 25 km/h

510,- 203 8900 Spare wheel mounting

SUPPORT FACILITIES:

91,- 203 6110 Support wheel with angular gear

323,- 202 6140 Semi trailer support winch with 2 speeds

448,- 203 6130 Hydraulic support foot with protected double-acting cylinder, pipe in pipe guide to accommodate the axial forces, with locking block for double-acting cylinder as standards (no shut-off valves required)