

10 YEARS WARRANTY ON CHASSIS FRAME

Perm. gross weight: 10,2 t, Payload 8 t
Platform size outside
4140 x 2150 x 500 + 500 mm
25 km/h

Technical data approx.:

Perm. gross weight:	10200 kg
	without airbrake system
	max 8000 kg permissible gross weight
Dead weight:	2190 kg
Platform size inside:	4070 x 2080 mm
Overall length:	5410 mm
Overall width:	2260 mm
Steel sideboards:	500 mm
Attachment boards:	500 mm
Track:	1550 mm
Axle cross section:	70 mm
Platform height:	1040 mm
Tyres:	13.0/75 - 16 (10) with tube
Tipping cylinder stage	3
Stroke length:	1400 mm
Cyl. diameter w. 1 cyl	75/90/105
Cyl. diameter w. 2 cyl	60/75/90
Max. operation press:	200 bar
Tipping angle lateral/l	45/45 Degrees
Required amount of c	8,5 / 12,6 l

Euro without

VAT	Art. Nr.	
11.069,-	204 0010	Basic price TA 10.041 version 1 lifting cylinder Austria with changing brake
12.597,-	204 0011	Basic price TA 10.041 version 1 lifting cylinder Germany with 2-line airbrake system
11.650,-	204 0000	Basic price TA 10.041 version 2 lifting cylinder Austria with changing brake
13.178,-	204 0001	Basic price TA 10.041 version 2 lifting cylinder Germany + 2-line airbrake system

Special equipment against extra charge

CHASSIS

Series 204 1110	Trailer coupling 25 km/h - 8t gross weight + adapter
206,-	204 1115 Trailer coupling over 25 km/h - 8 to gross weight
945,-	204 1130 Automatic trailer coupling including changed, rear transverse girder

BODY:

979,-	204 3200	2 nd set steel attachment boards 400 mm *)
1.156,-	204 3210	2 nd set steel attachment boards 500 mm *)
1.323,-	204 3220	2 nd set steel attachment boards 600 mm *)
293,-	204 3230	3 rd steel attachment boards 500 mm only rear
121,-	204 3120	Sideboard lifting springs left + right
265,-	204 3160	Collapsible attachment walls
71,-	204 3450	Tension chains (1 set per set walls)
419,-	204 3430	Set skewing pillars
131,-	204 3440	Set corner chains
41,-	204 3490	Potato slide (450 mm wide)
78,-	204 3596	View grille (perforated sheet) over the overall width instead of front attachment board
136,-	204 3598	View grille (perforated sheet) between stanchions with sheet metal cover
61,-	204 3460	Discharge channel not lockable
		Discharge channel with additional fine dosing:
142,-	204 3470	for grain slide
249,-	204 3475	for potato slide

Standard equipment:

Chassis:	V-frame made of C-pressed section 8 mm, trailer coupling (in Austria at single approving only for using inside factory), tandem axle with leaf spring mounted under the axes, control arm compensation and spring support, towing facility: (D/H: 40/31mm)
Platform frame:	V-trapezoidal tipping frame
Platform:	Platform with 5 mm steel plate base folded form one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 500 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 5 lateral and 4 rear, plugged corner stanchions, pivot board rear, with central locking lever, grain slide with adjusting lever
Swing attachments	1 st set steel swing attachments 500 mm high, with attachment corner stanchions
Tipping facility	Ball tipping mountings with conical socket, 3-stage lifting cylinder, 1400 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling, automatic stroke limitation, shut-off valve
Braking system:	Austria: Changing brake Germany: 2-line airbrake system
Support:	Support wheel, high-hinged and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity-primed sideboards, superstructure HB-green
Licence:	Austria: 25 km/h type certificate for agriculture Germany: 25 km/h operating permit agriculture

Euro without

VAT	Art. Nr.	
		BODY:
317,-	204 3500	Attachment triangles 300 mm high front and rear
3.059,-	204 3510	Tarpaulin body with roll-up tarpaulin , consisting of: Attachment triangles 300 mm front and rear, fixed tarpaulin bar, tarpaulin rolled from right to left with aluminium slat and operating platform with railing at the face end, Hydraulic support foot required (no space to crank)
293,-	204 3520	Hydraulic lateral swing sideboard plug-type unlocking left and right
370,-	204 3525	Upon subsequent delivery
287,-	204 3110	Swing sideboard le + ri + central locking lever
-777,-	204 3400	Price reduction: Supply without swing attachments

TIPPING INSTALLATION:

Series 204 5110	Shut-off valve	
4.092,-	204 5160	High tipping installation (approx. 750 mm higher, additional oil quantity required approx. 8 l) with own connection
410,-	204 5200	Rear hydraulic connection
145,-	204 5210	1 piece lifting cylinder 60/75/90/105 - 1600 mm, oil quantity, approx. 9 l, tipping angle approx. ° 45/50
291,-	204 5210	2 pieces lifting cylinder 60/75/90/105 - 1600 mm, oil amount approx 17,8 l tipping angle approx. ° 45/45

SILAGE BODIES:

3.986,-	204 4120	Silage body with hydraulic rear wall 1,500; grain tight, (with double-acting cylinder), including 2 nd swing attachment 500 mm, approx 12 m ³ , rear wall made of 4 mm steel plate, with grain slide, with plug-type rear hydraulic connection, view grille (perforated sheet) 4-stage lifting cylinder 1600 m
342,-	204 3234	Additional lower rear board with grain slide and corner stanchions 500mm height with closures
293,-	204 3235	Additional 1 st attachment board 500 mm rear with corner stanchions and closures
309,-	204 3237	Additional 1 st attachment board 600 mm rear + corner stanchions + closures

Euro without.

VAT Art. Nr.

BRAKING SYSTEM

Series Both axes braked
1.526,- 204 5615 2-line airbrake system (if not included in basic price)

359,- 204 5710 Rear connection with two-line air brake system

398,- 204 5750 ALB (automatic load-dependent brake force control) of the 2-line airbrake system (if not included in the quick runner packet)

726,- 204 5760 Hydraulic brake without load adaption valve

1.202,- 204 5765 Hydraulic brake with load adaption valve

QUICK RUNNER VERSIONS AUSTRIA

3.949,- 204 7100 **40 km/h-version:** behind agriculture tractors
2-line airbrake system with **ALB, 70 mm axes**, underride guard, mudguards, licence plate lighting, Tyres 355/60 R 18 MPT (16), contour lamps, white lamps front, gravel splash guard in the wheel area

6.827,- 204 7200 **60 km/h-version:** behind agriculture tractors
2-line airbrake system with **ALB, with ABS, automatic linkage adjuster, 70 mm axes**, underride guard, mudguards, licence plate lighting, Tyres 355/60 R 18 MPT (16) tbl., contour lamps front, gravel splash guards in the wheel area

7.371,- 204 7300 **80 km/h-version:** behind agriculture tractors
2-line airbrake system with **ALB, with ABS, (24 Volt)**, with automatic linkage adjuster, underride guard, mudguards, fog tail light, quick runner lighting system, tyres 355/60 R 18 MPT (16) tbl., contour light, white lamps front, gravel splash guards in the wheel area

QUICK RUNNER VERSIONS GERMANY

2.025,- 204 7101 **40 km/h-version** behind agriculture tractors:
2-line airbrake system, without ALB, without ABS, axes with brakes 300x80, Tyres 355/60 R 18 MPT (16), underride guard, gravel splash guard in the wheel area

2.025,- 204 7201 **60 km/h-version** behind agriculture tractors:
2-line airbrake system, without ALB, without ABS, axes with brakes 300x80, Tyres 355/60 R 18 MPT (16) tbl., underride guard, gravel splash guard in the wheel area

5.737,- 204 7301 **80 km/h-version** behind agriculture tractors:
2-line airbrake system, with ABS (24 voltage), with automatic linkage adjuster, underride guard, mudguards, fog tail light, quick runner lighting system tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

CAUTION: Required for non agriculture tractors.

424,- 204 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)

1.088,- 204 7520 AGS - automatic linkage adjuster for airbraked axes (not required in connection with agriculture tractors)

TYRES INSTEAD OF STANDARD TYRES:

108,- 204 8150 15.0/55 - 17 (10) tbl.

507,- 204 8280 355/60 R 18 MPT (16) tbl.

823,- 204 8290 340/65 R 18 (16) Mich. Steel case Tbl.

-404,- 204 8120 Price reduction: 11.5/80 - 15.3 (10) with tube

510,- 204 8900 Spare wheel mounting

Euro without

VAT Art. Nr.

TYRES INSTEAD OF STANDARD TYRES:

none-retrofit tyres:

1.225,- 207 8182 **with 25 km/h:** 505/50 R 17 MPT tbl., with doublehump-security rim (corresponds 16 ply)

2.061,- 207 8183 **bei 40 km/h:** (lateral sideboard only swing possible) incl. 90 mm axes

SUPPORT FACILITIES:

91,- 204 6110 Support wheel with angular gear

145,- 204 6120 Support winch mechanical max. 1000 kg support

323,- 204 6140 Semi trailer support winch with 2 speeds

448,- 204 6130 Hydraulic support foot with protected double-acting cylinder, pipe in pipe guide to accommodate the axial forces, with locking block for double-acting cylinder as standards (no shut-off valves required)

761,- 204 6150 Hydraulic support "sloping" with protected single-acting cylinder (cylinder can not be attached while attaching, only single-acting control device necessary)

