

10 YEARS WARRANTY ON CHASSIS FRAME

**Permissible gross weight A/G: 10 / 11 to
Payload: 7,4 / 8,4 to
Platform size outside
4550 x 2220 x 500 + 500 mm 25 km/h**

Technical data approx.:

Permissible gross we A/G:	10000/11000
	without airbrake system
	max 8000 kg perm. gross weight
Dead weight:	2620 kg
Platform size inside:	4480 x 2150 mm
Overall length:	6330 mm
Overall width:	2360 mm
Steel sideboards:	500 mm
Attachment boards:	500 mm
Track:	1600 mm
Axle cross section:	70 mm
Platform height:	1050 mm
Tyres:	13.0/75 - 16 (10) with tube
Tipping cylinder stage	4
Stroke length:	1600 mm
Cyl. diameter 1 cyl.:	75/90/105/120
Max. operating press:	200 bar
Tipping angle lateral/i	45/45 Degrees
Required amount of c	12,6 l

Euro without

VAT	Art. Nr.	
12.185,-	205 0000	Basic price TA 11.045 version Austria with changing brake (10 t PGW)
13.713,-	205 0001	Basic price TA 11.045 version Germany with two-line airbrake (11 t PGW)
		Special equipment against extra charge

CHASSIS:

Series 205 1110	Trailer coupling 25 km/h - 8 to PGW
206,-	205 1115 Trailer coupling over 25 km/h - 8 to PGW
945,-	205 1130 Automatic trailer coupling including changed rear transverse girder

BODY:

150,-	205 3240	Steel sideboards 600 mm instead of 500 mm
150,-	205 3340	Steel attachment boards 600 mm instead of 500 mm
979,-	205 3200	2 nd set steel attachment boards 400 mm *)
1.156,-	205 3210	2 nd set steel attachment boards 500 mm *)
1.323,-	205 3220	2 nd set steel attachment boards 600 mm *)
293,-	205 3230	3 rd steel attachment board 500 mm only rear
121,-	205 3120	Sideboard lifting springs left + right
265,-	205 3160	Collapsible attachment walls
287,-	205 3110	Swing sideboard le +ri with central locking lever
71,-	205 3450	Tension chains (1 set per set walls)
419,-	205 3430	Set skewing pillars with corner chains
131,-	205 3440	Set corner chains
41,-	205 3490	Potato slide (450 mm wide)
78,-	205 3596	View grille (perforated sheet) over the overall width instead of front attachment board
136,-	205 3598	View grille (perforated sheet) between the stanchions with sheet metal cover
61,-	205 3460	Discharge channel not lockable
		Discharge channel with additional fine dosing
142,-	205 3470	for grain slide
249,-	205 3475	for potato slide
317,-	205 3500	Attachment triangles 300 mm high front and rear
293,-	205 3520	Hydraulic lateral swing sideboard plug-type unlocking left and right

Standard equipment

Chassis:	V-frame made of C-pressed sections 8 mm, trailer coupling (in Austria at single approving only for using inside factory), tandem axle with leaf spring, control arm compensation and spring support, towing facility: (D/H: 40/31mm)
Platform frame:	V-trapezoidal tipping frame
Platform:	Platform with 5 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 500 mm with skirting board 70 mm, cavity priming, sideboard hinges: 6 lateral and 4 rear, plugged corner stanchions, pivot board rear with central locking lever, grain slide with adjusting lever
Swing attachments:	1 st set steel attachment boards 500mm with attachment corner stanchions
Tipping facility:	Ball tipping mountings with conical socket, 1 piece. 4-stage lifting cylinder, 1600 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling, automatic stroke limitation
Brake installation:	Austria: Changing brake Germany: 2-line airbrake system
Support:	Support wheel collapsible and adjustable in height
Electricity	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity-primed sideboards, superstructure HB-green
Licence:	Austria: 25 km/h type certificate agriculture Germany: Operating permit 25 km/h agriculture

Euro without

VAT	Art. Nr.	
		<u>BODY:</u>
3.059,-	205 3510	Tarpaulin body with roll-up tarpaulin , consisting of: Attachment triangles 300 mm front and rear, fixed tarpaulin bar, tarpaulin rolled from right to left with aluminium slat and operating platform with railing at the face end
-777,-	205 3400	Price reduction: Delivery without swing attachments

TIPPING INSTALLATION

Series 205 5110	Shut-off valve	
5.174,-	205 5160	High tipping installation (approx. 750 mm higher, additional oil quantity required approx. 11l) with own connection
410,-	205 5200	Rear hydraulic connection
104,-	205 5325	Lifting cylinder 75/90/105/120 - 1800 mm, oil amount approx. 15 l, tipping angle approx. °45/50

SILAGE BODIES:

3.293,-	205 4120	Silage body with hydraulic rear wall 1500 mm, grain tight, (with double-acting cylinder), including 2 nd swing attachment 500 mm, approx. 15 m ³ , rear wall made of 4 mm steel plate with grain slide, with plug-type rear hydraulic connection, view grille (perforated sheet), 4-stage lifting cylinder 1800 m
342,-	205 3234	Additional lower rear board with grain slide and corner stanchions, 500 mm height with closures
293,-	205 3235	Additional 1 st attachment board 500 mm rear with corner stanchions and closures
309,-	205 3237	Additional 1 st attachment board 600 mm rear + corner stanchions + closures

BRAKING SYSTEMS:

2.102,-	205 5615	Two-line airbrake instead of changing brake for 25 km/h 11 to gross weight with tyres 355/60 R 18 MPT (only for Austria)
359,-	205 5710	Rear connection for two-line air brake system

Euro without
VAT Art. Nr.

BRAKING SYSTEMS:

398,- 205 5750 ALB (automatic load-dependent brake force control) of the 2-line airbrake system (if not included in the quick runner packet)

726,- 205 5760 Hydraulic brake without load adaptation valve (10 km/h)

1.202,- 205 5765 Hydraulic brake with load adaption valve (10 km/h)

QUICK RUNNER VERSIONS AUSTRIA

4.055,- 205 7100 **40 km/h-version** behind agriculture tractors: 11 t gross weight, 2-line airbrake system with **ALB**, axes, underride guard, mudguards, licence plate lighting, Tyres 355/60 R 18 MPT (16), contour lamps, side marker lamps, white lamps front, gravel splash guard in the wheel area

7.309,- 205 7200 **60 km/h-version** behind agriculture tractors: 11 t gross weight, 2-line airbrake system with **ALB**, with **ABS (24 voltage)**, **automatic linkage adjuster**, axes, underride guard, mudguards, licence plate lighting, Tyres 355/60 R 18 MPT (16) tbl., contour lamps, side marker lamps, white lamps front, gravel splash guard in the wheel area

8.440,- 205 7300 **80 km/h-version** behind agriculture tractors: 2-line airbrake system with **ALB**, with **ABS (24 voltage)**, with automatic linkage adjuster, underride guard, mudguards, fog tail light, quick runner lighting system, tyres 355/60 R 18 MPT (16) tbl., contour lamps, side marker lamps, white lamps front, gravel splash guard in the wheel area

QUICK RUNNER VERSIONS GERMANY

1.405,- 205 7101 **40 km/h-version** behind agriculture tractors: 2-line airbrake system, 70 mm axes with brake 300x80, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16), gravel splash guard in the wheel area

1.942,- 205 7201 **60 km/h-version** behind agriculture tractors: 2-line airbrake system, 80 mm axes, brake 350x80/8, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

5.160,- 205 7301 **80 km/h-version** behind agriculture tractors: 2-line airbrake system with ALB, with ABS (24 V), with automatic linkage adjuster, 80 mm axes, brake 350x80/8, underride guard, mudguards, fog tail lamp, 7 pole, 24 voltage, quick runner lighting system, support weight max 1000 kg, Tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

CAUTION: Required for non agriculture tractors:

424,- 205 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)

1.088,- 205 7520 AGS - automatic linkage adjuster for airbraked axes (not required in connection with agriculture tractors)

TYRES INSTEAD OF STANDARD TYRES:

108,- 205 8150 15.0/55 - 17 (10) tbl.

477,- 205 8270 275/65 R 18 Michelin tbl.

511,- 205 8280 355/60 R 18 MPT (16) tbl.

823,- 205 8290 340/65 R 18 (16) Mich. Steel case Tbl.

510,- 205 8900 Spare wheel mounting

Euro without
VAT Art. Nr.

TYRES INSTEAD OF STANDARD TYRES:

None-retrofit tyres:

1.225,- 207 8182 **with 25 km/h:** 505/50 R 17 MPT tbl., with double-hump-security rim (corresponds 16 ply)

2.061,- 207 8183 **with 40 km/h:** (lateral sideboard only swinging possible) incl. 90 mm axes

SUPPORT FACILITIES:

91,- 205 6110 Support wheel with angular gear

145,- 205 6120 Support winch mech. max. 1000 kg support weight

323,- 205 6140 Semi trailer support winch with 2 speeds

448,- 205 6130 Hydraulic support foot with protected double-acting cylinder, pipe in pipe guide to accommodate the axial forces, with locking block for double-acting cylinder as standards (no shut-off valves required)

761,- 205 6150 Hydraulic support "sloping" with protected single-acting cylinder (cylinder can not be damaged while attaching, only single-acting control device necessary)