

BRANTNER

TANDEM THREE-SIDED TIPPER TA 11 045 XXL

10 YEARS WARRANTY ON CHASSIS FRAME

Permissible gross weight: 11 to, Payload: 8,3
Platform size outside:
4550 x 2220/2320 x 500 + 500 mm
Swing board left, right, rear

Technical data approx:

Permissible gross weight:	11000 kg
Dead weight:	2750 kg
Platform size inside:	4480 x 2150/2250 mm
Overall length:	6330 mm
Overall width:	2420 mm
Steel sideboards:	500 mm
Attachment boards:	500 mm
Track:	1800 mm
Spring distance:	1230 mm
Axle cross section:	70 mm
Platform height:	1160 mm
Tyres:	13.0/75 - 16 (10)
Tipping cylinder stage:	3/4
Stroke length:	1600 / 1600 mm
Cyl. diameter w. 1 cyl:	75/90/105/120
Cyl. diameter w. 2 cyl:	60/75/90/105
Max. operating pressure:	200 bar
Tipping angle lateral/rear:	45/45 Degrees
Required amount of oil:	12/18 l

Euro without

VAT	Art. Nr.	
13.702,-	206 0000	Basic price TA 11.045 XXL with 1 cylinder with two-line airbrake system
14.330,-	206 0001	Basic price TA 11.045 XXL with 2 cylinders with two-line airbrake system

Special equipment against extra charge

CHASSIS:

206,-	206 1115	Trailer coupling 25 km/h - 8t gross weight
945,-	206 1130	Automatic trailer coupling included changed, rear transverse girder
265,-	206 1116	Track 1950 mm, axle cross section 80 mm
Series 206	1220	Bugle adjustable in height
198,-	206 1190	Gravel splash protection in the wheel area
687,-	206 1211	springs under axle, platform height ca. 105 cm

BODY:

150,-	206 3240	Steel sideboard 600 mm instead of 500 mm
150,-	206 3340	Steel attachment boards 600 instead of 500 mm
979,-	206 3200	2 nd set steel attachment boards 400 mm *)
1.156,-	206 3210	2 nd set steel attachment boards 500 mm *)
1.323,-	206 3220	2 nd set steel attachment boards 600 mm *)
293,-	206 3230	3 rd steel attachment board 500 mm only rear
309,-	206 3420	Steel sideboards 2.5 mm instead of 2 mm per set
121,-	206 3120	Sideboard lifting springs left + right
300,-	206 3370	Collapsible attachment boards (platform 2320 mm - not conical)
71,-	206 3450	Tension chains (1 set per set walls)
419,-	206 3430	Set skewing pillars with corner chains
131,-	206 3440	Set corner chains
41,-	206 3490	Potato slide (450 mm wide)
1.540,-	206 3599	Split sideboard + attachment board left and right with screw-type centre stanchions
78,-	206 3596	View grille (perforated sheet) over the overall width instead of front attachment board

Standard equipment:

Chassis:	Frame made of high-stable G-pressed sections 225 x 100, 8 mm thick, with stable underride guard, with cross stiffening, trailer coupling (in Austria at single approving only for using inside factory), tandem axle with leaf spring, control arm compensation and spring support, bugle adjustable in height DIN 74054, towing facility: (D/H: 40/31 mm)
Platform frame:	V-trapezoidal tipping frame
Platform:	Conical platform with 5 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 500 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 6 lateral and 4 rear, plugged corner stanchions, swing board left/right and rear with central locking lever and closing hook for 30 mm latching range, large closures, grain slide with adjusting lever
Swing attachments:	1 st set steel attachment boards 500mm high, with attachment corner stanchions
Tipping facility:	Ball tipping mountings with conical socket, 3/4-stage lifting cylinder, 1600 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling and shut-off valve, automatic stroke limitation
Brake installation:	Two-line airbrake system, fourwheel braked
Support:	Support wheel, high-hinged and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting cavity-primed sideboards, superstructure HB green
Licence:	Austria: 25 km/h type certificate, for agriculture Germany: Operating permit 25 km/h agriculture

Euro without

VAT	Art. Nr.	
BODY:		
136,-	206 3598	View grille (perforated sheet) between stanchions with sheet metal cover
61,-	206 3460	Discharge channel not lockable
		Discharge channel with additional fine dosing
142,-	206 3470	for grain slide
249,-	206 3475	for potato slide
317,-	206 3500	Attachment triangles 300 mm high front and rear
1.960,-	206 3515	Tarpaulin body with rolled-up tarpaulin consisting of: Attachment triangles 300 mm front +rear, folding-type tarpaulin bar, tensioning straps, tarpaulin rolled from right to left + aluminium slat + operating platform with railing at the face end
2.114,-	206 3514	Tarpaulin body with roll-up tarpaulin, consisting of: Attachment triangles 300 mm front and rear, folding-type tarpaulin bar, tensioning straps, tarpaulin rolled from left to right (access ladder on the right) with aluminium slat and operating platform with railing at the face end
293,-	206 3520	Hydraulic lateral swing sideboard plug-type unlocking left and right
370,-	206 3525	Upon subsequent delivery
1.023,-	206 3530	Hydraulic swing sideboard unlocking rear
3.214,-	206 3540	Hydraulic lateral 180° sideboard opening and closing (additional double-acting control unit required on tractor)

415,-	206 3570	Stable chute lateral approx 360 mm high per side, for opening jointly with lateral swing sideboard unlocking (only with track 1800 mm possible)
250,-	206 3410	Sideboard stiffening left and right per set

-931,-	206 3400	Price reduction: Supply without swing attachments
--------	----------	---

SILAGE BODIES

3.397,-	206 205	Silage body with hydraulic rear wall 1500 mm, grain tight, (with double-acting cylinders), including 2 nd swing attachment 600 mm, approx 15 m³, rear wall made of 4 mm steel plate, with grain slide, with plug-type rear hydraulic connection, view grille (perforated sheet), 4-stage lifting cylinder 1800 mm
---------	---------	--

Euro without
VAT Art. Nr.

SILAGE BODIES

3.998,- 206 4136 Silage body with hydraulic rear wall 1800 mm high, grain-tight, (with double-acting cylinders, including 2nd swing attachment 600 mm, as well as rise of the sideboard and attachment board of 500 on 600 mm, approx 18m³, rear wall made of 4 mm steel plate, with grain slide, with plug-type rear hydraulic connection, view grille (perforated sheet), 4-stage lifting cylinder 1800 mm lift

342,- 206 3234 Additional lower rear board with grain slide + corner stanchions for 500 mm height with closures

293,- 206 3235 Additional 1st attachment board 500 mm rear with corner stanchions and closures

359,- 206 3238 Additional lower rear board with grain slide + corner stanchions for 600 mm height including closures

309,- 206 3237 Additional 1st attachment board 600 mm rear + corner stanchions + closures

206 3512 Tarpaulin body with roll-up tarpaulin
**in combination with hydraulic rear wall
LOOK AT PAGE 45**

162,- 206 3513 Supports for hydraulic rear wall (support left and right to support the hydraulic rear wall with uppermost attachment wall folded down)

TIPPING INSTALLATION:

Series 206 5110 Shut-off valve

Lifting cylinder 75/90/105/120-1800 mm, oil amount cylinder 5 l, tipping angle approx °45/49

104,- 206 5325 with 1 cylinder:

Lifting cylinder 60/75/90/105-1800 mm, oil amount per cylinder 11 l, tipping angle approx 45/49

140,- 206 5311 with 2 cylinders:

5.174,- 206 5160 High tipping installation (approx 750 mm higher, additional oil quantity required approx 11l) with own connection

410,- 206 5200 Rear hydraulic connection

BRAKING SYSTEMS:

o. MP 206 5630 1-line airbrake system instead of 2-line airbrake (only permitted up to 25 km/h)

208,- 206 5640 Combined 1- and 2-line airbrake system instead of two-line airbrake system (permitted up to 25 km/h)

359,- 206 5710 Rear connection with two-line airbrake system

280,- 206 5730 Rear connection with one-line airbrake system

426,- 206 5740 Rear connection with 1- and 2-line airbrake system

510,- 206 5741 Rear connection for combined one and two-line air brake with one-line trailer control valve

398,- 206 5750 ALB (automatic load-dependent brake force control) of the 2-line airbrake system (if not included in the quick runner packet)

QUICK RUNNER VERSIONS AUSTRIA

2.527,- 206 7100 **40 km/h-version** behind agriculture tractors: 2-line airbrake with **ALB, 70 mm axes**, underride guard, mudguards, licence plate lighting tyres 355/60 R 18 MPT (16), contour light, side marker lamps, white lamps front, gravel splash guard in the wheel area, wheel covering, without trailer coupling

Euro without
VAT Art. Nr.

QUICK RUNNER VERSIONS AUSTRIA

5.780,- 206 7200 **60 km/h-version** behind agriculture tractors: 2-line airbrake system with **ALB, with ABS (24 voltage), automatic linkage adjuster 70 mm axes**, underride guard, mudguards, licence plate lighting, tyres 355/60 R 18 MPT (16) tbl., contour lamps, side marker lamps, white lamps front, gravel splash guard in the wheel area

6.361,- 206 7300 **80 km/h-version** behind agriculture tractors.: 2-line airbrake with **ALB, with ABS**, with automatic linkage adjuster, underride guard, mudguards, licence plate lighting, quick runner lighting system, tyres 355/60 R 18 MPT (16) tbl., contour lamps, side marker lamps, white lamps front, gravel splash guard in the wheel area

QUICK RUNNER VERSIONS GERMANY

1.802,- 206 7101 **40 km/h-version** behind agriculture tractors: 2-line airbrake system, ALB, 80 mm axes with brake 300x90, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

1.802,- 206 7201 **60 km/h-version** behind agriculture tractors: 2-line airbrake system, ALB, 80 mm axes, brake 300x90, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

5.160,- 206 7301 **80 km/h-version** behind agriculture tractors: 2-line airbrake system with ALB, with ABS (24 voltage), with automatic linkage adjuster, 80 mm axes, brake 350x80/8, underride guard, mudguards, fog tail lamp, 7-pole, (24 voltage), quick runner lighting system, support weight max. 1000 kg, tyres 355/60 R 18 MPT (16) tbl., gravel splash guard in the wheel area

0,- 206 7810 Standardization of 10 to permissible gross weight (no six month security inspection)

287,- 206 7530 Bugle for support weight over 1000 kg to 1800 kg (only for agriculture area) for 40 and 60 km/h

CAUTION: Required for non agriculture tractors:

424,- 206 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)

813,- 206 7520 AGS - autom. linkage adjuster airbraked axes

TYRES INSTEAD OF STANDARD TYRES:

108,- 206 8150 15.0/55 - 17 (10)

507,- 206 8280 355/60 R 18 MPT (16)

823,- 206 8290 340/65 R 18 (16) Mich. Steel case

510,- 206 8900 Spare wheel mounting

None-retrofit tyres:

1.592,- 206 8160 **with 25 km/h:** 19.0/45 - 17 (10), track 1950 mm Axle cross section 80 mm (brake drum 300x80)

847,- 206 8161 **with 40 km/h:**

1.953,- 206 8170 **with 25 km/h:** 500/50 - 17 (10), Track 1950 mm, axle cross section 80 mm

1.208,- 206 8171 **with 40 km/h:**

1.710,- 206 8182 **with 25 km/h:** 505/50 R 17 MPT, Track 1950 mm, axes square 80 mm

963,- 206 8183 **with 40 km/h:**

SUPPORT FACILITIES:

91,- 206 6110 Support wheel

145,- 206 6120 Support winch mechanical

323,- 206 6140 Semitrailer support winch with 2 speeds

448,- 206 6130 Hydraulic support foot with protected double-acting cylinder, pipe in pipe guide to accommodate the axial forces, with locking block for double -acting cylinder as standards (no shut-off valves required)