

BRANTNER TA 13 045/2

TANDEM THREE SIDED TIPPER

10 YEARS WARRANTY ON CHASSIS FRAME

Permissible gross weight: 12,6 t, PL: 10 t
Platform size outside:
4550 x 2220 x 600 + 600 mm
2-line airbrake

Technical data approx.:

Permissible gross wei	12600 kg
Dead weight:	2605 kg
Platform size inside:	4480 x 2150 mm
Overall length:	6330 mm
Overall width:	2360 mm
Steel sideboards:	600 mm
Attachment boards:	600 mm
Track:	1600 mm
Axle cross section:	80 mm
Platform height:	1050 mm
Tyres:	355/60 R 18 MPT (16)
Tipping cylinder stage	4
Stroke length:	1600 mm
Cyl. diameter with 2 c:	60/75/90/105
Max. operating pressu	200 bar
Tipping angle lateral/r	45/43 degrees
Required amount of o	18 l

Euro without

VAT	Art. Nr.	
15.844,-	207 0000	Basic price TA 13.045/2 with 2 lifting cylinders with two-line-airbrake system
o. MP		Germany: vehicle certificate 25 km/h (for agriculture not required)

Special equipment against extra charge

CHASSIS:

Series 207 1110	Trailer coupling 25 km/h - 8 t gross weight
206,- 207 1115	Trailer coupling over 25 km/h - 8 to gross weight
945,- 207 1140	Automatic trailer coupling (including changed, rear transverse girder)
Series 207 1220	Bugle adjustable in height
96,- 207 7530	Bugle for support weight until 1800 kg (DIN 11026)
1.912,- 207 1240	Spring born tow bar
198,- 207 1190	Gravel splash guard in the wheel area

PLATFORM

270,- 207 2030	Platform 4480 x 2150/2250 mm inside - conical
1.519,- 207 2130	Platform 5040 x 2150/2250 mm inside - conical

BODY:

-168,- 207 3260	Price reduction: Sideboard 500 mm instead of 600 mm
-136,- 207 3360	Price red.: Attachment board 500 mm instead 600 mm
979,- 207 3200	2 nd set steel attachment boards 400 mm *)
1.156,- 207 3210	2 nd set steel attachment boards 500 mm *)
1.323,- 207 3220	2 nd set steel attachment boards 600 mm *)
293,- 207 3230	3 rd steel attachment board 500 mm only rear
309,- 207 3420	Steel sideboards 2,5 mm instead of 2 mm per set
287,- 207 3110	Swing sideboard left + right+central locking lever
121,- 207 3120	Sideboard lifting springs left + right
265,- 207 3160	Collapsible attachment boards
71,- 207 3450	Tension chains (1 set per set walls)
419,- 207 3430	Set skewing pillows with corner chains
1.540,- 207 3599	Split sideboard + attachment board left and right with screwtype centre stanchions
131,- 207 3440	Set corner chains
41,- 207 3490	Potato slide (450 mm wide)
78,- 207 3596	View grille (perforated sheet) over the overall width instead of front attachment board

Standard equipment:

Chassis:	Frame made of high-stable G-pressed sections 8 mm, trailer coupling (in Austria at single approving only for using inside factory), tandem axle with leaf spring mounted under the axles, control arm compensation and spring support, towing facility: (D/H: 40/31mm)
Platform frame:	V- trapezoidal tipping frame
Platform:	Platform with 5 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 600 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 6 lateral and 4 rear, plugged corner stanchions, pivot board rear with central locking lever, grain slide with adjusting lever
Swing attachments:	1 st set steel attachments boards 600 mm high, with attachment corner stanchions
Tipping facility:	Ball tipping mountings with conical socket, 2 pieces, 4-stage lifting cylinder, 1600 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling and shut -off valve, automatic stroke limitation
Brake installation:	Two-line-airbrake system, fourwheel braked
Support:	Support wheel, high-hinged and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting cavity-primed sideboards, superstructure HB green
Licence:	Austria: 25 km/h type certificate for agriculture Germany: Operating permit 25 km/h agriculture

Euro without

VAT Art. Nr.

BODY:		
136,- 207 3598	View grille (perforated sheet) between stanchions with sheet metal cover	
61,- 207 3460	Discharge channel not lockable	
317,- 207 3500	Attachment triangles 300 mm high front and rear	
	Discharge channel with additional finde dosing	
142,- 207 3470	for grain slide	
249,- 207 3475	for potato slide	
1.960,- 207 3515	Tarpaulin body with roll-up tarpaulin , consisting of: Attachment triangles 300 mm front and rear, folding-type tarpaulin bar, tensioning straps, tarpaulin rolled from right to left + aluminium slat + operating platform with railing at the face end	
2.114,- 207 3511	Tarpaulin body with roll-up tarpaulin, consisting of Attachment triangles 300 mm front and rear, folding-type tarpaulin bar, tensioning straps, tarpaulin rolled from left to right (access ladder on the right) with aluminium slat and operating platform with railing at the face end	
293,- 207 3520	Hydraulic lateral swing sideboard plug-type unlocking left and right	
1.023,- 207 3530	Hydraulic swing sideboard unlocking rear	
3.214,- 206 3540	Hydraulic lateral 180° sideboard opening and closing (additional double-acting control unit required on tractor)	
415,- 207 3570	Stable chute lateral approx. 360 mm high per side, for opening jointly with lateral swing sideboard unlocking (only possible with a track 1800 mm)	
250,- 207 3410	Sideboard stiffening left and right per set	
-931,- 207 3400	Price reduction: Delivery without swing attachments	
SILAGE BODIES:		
3.733,- 207 4136	Silage body with hydraulic rear wall 1,800 mm high, grain-tight, with double-acting cylinders, including 2 nd swing attachment 600 mm, ca. 18m ³ , rear wall made of 4 mm steel plate, with grain slide, with plug-type rear hydraulic connection, view grille (perforated sheet), 4-stage lifting cylinder 1800 mm lift	
359,- 207 3239	Additional lower rear board with grain slide and corner stanchions for 600 mm height incl. closures	

Euro without
VAT Art. Nr.

SILAGE BODIES:

309,- 207 3237 Additional 1st attachment board 600 mm rear with corner stanchions and closures

207 3512 Tarpaulin body with roll-up tarpaulin
in combination with hydraulic rear wall
LOOK AT PAGE 45

162,- 207 3513 Supports for hydraulic rear wall (supports left and right to support the hydraulic rear wall with uppermost attachment wall folded down)

TIPPING INSTALLATION:

Series 207 5110 Shut-off valves

212,- 207 5326 Lifting cylinder 75/90/105/120-1800 mm, oil quantity per cylinder 15 l, tipping angle approx. °45/49 with 2 cylinder

140,- 207 5311 Lifting cylinder 60/75/90/105-1800 mm, oil quantity per cylinder 11 l, tipping angle approx. °45/49 with 2 cylinder

5.174,- 207 5160 High tipping installation (approx. 750 mm higher, additional oil quantity required approx. 11l) with own connection

410,- 207 5200 Rear hydraulic connection

BRAKING SYSTEMS:

208,- 207 5640 Combined 1-and 2-line air brake system instead of 2-line air brake system (only permitted up to 25 km/h)

359,- 207 5710 Rear connection with 2-line air brake system

280,- 207 5730 Rear connection with 1-line air brake system

426,- 207 5740 Rear connection with 1 + 2-line air brake system

510,- 207 5741 Rear connection with combined 1 and 2-line air brake with 1-line trailer control valve

398,- 207 5750 ALB (automatic load-dependent brake force control) of the 2-line air brake system (if not included in quick runner packet)

QUICK RUNNER VERSIONS AUSTRIA

1.646,- 207 7100 **40 km/h-version** behind agriculture tractors:
2-line air brake system with **ALB, 80 mm axes**, Brake: 300x90/8, underride guard, mudguards, tyres 355/60 R 18 MPT (16), contour lamps, side marker lamps, white lamps front, gravel splash guard in the wheel area, wheel covering, without trailer coupling

9.432,- 207 7300 **80 km/h-version** behind agriculture tractors:
2-line air brake system with **ALB, with ABS (24 voltage) with automatic linkage adjuster 90 mm axes, brake 400x120**, underride guard, mudguards, fog tail lamp, quick runner lighting system, contour light, side marker lamps, white lamps front, tyres 385/55 R 19,5 la new, gravel splash guard in the wheel area



Euro without
VAT Art. Nr.

QUICK RUNNER VERSIONS GERMANY

592,- 207 7101 **40 km/h-version** behind agriculture tractors:
2-line air brake, 80 mm axes with brake 300x90/8, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, axes with manual linkage adjuster and membran cylinder, tyres 355/60 R 18 MPT (16) gravel splash guard in the wheel area

592,- 207 **60 km/h-version** behind agriculture tractors:
2-line air brake, 80 mm axes with brake 300x90/8, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, axes with manual linkage adjuster and membran cylinder, tyres 355/60 R 18 MPT (16) gravel splash guard in the wheel area, perm. gross weight 12.500 kg

8.233,- 207 7301 **80 km/h-version** behind agriculture tractors:
2-line air brake with **ALB, with ABS (24 voltage) with automatic linkage adjuster, 90 mm Achsen, Brake 400x120**, underride gurad, mudguards, fog tail lamp, 7polig (24 Volt) quick runner lighting system, Tyres 385/55 R 19,5 la new, gravel splash guard in the wheel area

CAUTION: Requird for non agriculture tractors:

424,- 207 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)

700,- 207 7520 AGS - autom. linkage adjuster for airbraked axes

TYRES INSTEAD OF STANDARD TYRES:

None-retrofit tyres:

715,- 207 8182 **with 25 km/h:** 505/50 R 17 MPT, Stroke length: 1600mm; with Doppelhump-Sicherheitsfelge (corresponds 16 nh)

1.388,- 207 8183 **with 40 km/h:** (lateral sideboard only swinging possible) incl. 90 mm axes

510,- 207 8900 Spare wheel mounting for tyres 355/60 R 18 on the forehead wall

SUPPORT FACILITIES:

91,- 207 6110 Support wheel with angular gear

323,- 207 6140 Semi trailer winch with 2 speeds

448,- 207 6130 Hydraulic support foot with protected double-acting cylinder, pipe in pipe guide to accommodate the axial forces, with locking block for double-acting cylinder as standards (no shut-off valves required)

761,- 207 6150 Hydraulic support "sloping" with protected single-acting cylinder (cylinder can not be damaged while attaching, only single-acting control device necessary)

