

BRANTNER TANDEM THREE-SIDED TIPPER TA 11 045 Low loader

10 YEARS WARRANTY ON CHASSIS FRAME

Perm. gross weight: 11 to, PL approx. 8,4 to
Platform size outside:
4550 x 2440/2450 x 500 mm
25 km/h 2-line airbrake

Technical data approx.:

Permissible gross weight	11000 kg
Dead weight:	2600 kg
Platform size inside:	4480 x 2370/2380 mm
Overall length:	6320 mm
Overall width:	2550 mm
Steel sideboards:	500 mm
Attachment boards:	-
Track:	1950 mm
Axle cross section:	70 mm
Platform height:	900 mm
Tyres:	215/75 R 17.5 (18) tbl.
Tipping cylinder stages:	4
Stroke length:	1600 mm
Cylinder diameter:	75 / 90 / 105 / 120 mm
Max. operating pressure:	200 bar
Tipping angle lateral/rear:	45/45 degrees
Required amount of oil	13,6 l

Euro without

VAT Art. Nr.

18.127,- 220 0000 **Basic price TA 11.045 low loader**

o. MP Vehicle certificate 25 km/h
(not required for agriculture)

Special equipment against extra charge

CHASSIS:

Series 220 1230	Flange towing eye adjustable in height
1.976,- 220 1250	Trailer tow bar adjustable in height by means of spindle around 250 mm
454,- 220 1300	Folding supports rear
-956,- 220 1510	Chassis with moving-automatism brake installation f. 8000 kg gross weight instead of airbrake syst. (G)
198,- 220 1190	Gravel splash guard in the wheel area

PLATFORM:

631,- 220 2174	Platform broadening 4480 x 2410 mm
1.551,- 220 2158	Platform 5040 x 2380 mm inside
1.988,- 220 2420	Aluminium ramps: length 3,2 m, width 400 mm load force 5700 kg/pair
323,- 220 2300	Steel base 5 mm instead of 4 mm
139,- 220 2430	Fixing eye per pair (sunk into base)

BODY:

136,- 220 3340	Steel attachment boards 600 instead of 500 mm
894,- 220 3130	Steel attachment boards 400 mm *)
1.069,- 220 3140	Steel attachment boards 500 mm *)
1.236,- 220 3150	Steel attachment boards 600 mm *)
309,- 220 3420	Steel sideboards 2,5 mm instead of 2 mm per set
121,- 220 3120	Sideboard lifting springs left + right
71,- 220 3450	Tension chains (1 set per set walls)
131,- 220 3440	Set corner chains
61,- 220 3460	Discharge channel not lockable
142,- 220 3470	Discharge channel with additional fine dosing (only for grain slides)
250,- 220 3410	Sideboard stiffening left and right per set

Standard equipment

Chassis:	V-frame made of closed C-pressed section frame 8 mm, with stable underride guard, tandem axle with leaf suspension, control arm compensation and spring support, springs mounted under axle, slide-in cart channel for aluminium-ramps with 3,2 m length, towing facility: (D/H: 40/31mm)
Platform frame:	V-trapezoidal tipping frame
Platform:	Platform with 4 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 500 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 6 lateral and 4 rear, plugged corner stanchions, pivot board left/right and rear, with central locking lever and closing hook for 30 mm latching range, large closures, grain slide with adjusting lever
Swing attachments:	-
Tipping facility:	Ball tipping mounting with conical socket, 4-stage lifting cylinder, 1600 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling and shut-off valve, automatic stroke limitation
Brake installation:	2-line airbrake, fourwheel braked
Support:	Support wheel, high-hinged and adjustable in height
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity primed sideboards, superstructure HB-green
Licence:	Austria: 25 km/h type certificate for agriculture Germany: 25 km/h operating permit agriculture

Euro without

VAT Art. Nr.

TIPPING INSTALLATION:

Series	Shut-off valve
Series	Lifting cylinder 75/90/105/120 - 1600 mm, oil quantity approx 13,6 l, tipping angle approx. ° 45/45

BRAKING SYSTEMS:

0,- 220 5630	1-line airbrake system instead of 2-line airbrake system
208,- 220 5640	Comb. 1- & 2-line airbrake instead of 2-line airbrake
359,- 220 5710	Rear connection with 2-line airbrake system
280,- 220 5730	Rear connection with 1-line airbrake system
426,- 220 5740	Rear connection with 1-and 2-line airbrake system
398,- 220 5750	ALB (automatic load-dependent brake force control) of the 2-line airbrake system (if not included in the quick runner packet)

QUICK RUNNER VERSION AUSTRIA

2.402,- 220 7100	40 km/h-version behind agriculture tractors: 2-line airbrake with ALB , axes + brake: 300x80/6, man. linkage adjuster, underride guard, mudguards, licence plate lighting, contour lamps, white lamps front, gravel splash guard in the wheel area
6.512,- 220 7200	60 km/h version behind tractors: 2-line brake, with ALB, AGS, ABS, 80 mm axes, brake 350x80/6, underride guard, mudguards, licence plate lighting, tyres 245/70 R 17.5 (18) tbl., contour and side marker lamps, white lamps front, gravel splash guard in the wheel area
7.089,- 220 7300	*80 km/h version: behind tractors: 2-line brake, with ALB, AGS, ABS, 80 mm axes, brake 350x80/6, underride guard, mudguards, fog tail lamp, licence plate lighting, tyres 245/70 R 17.5 (18) tbl., contour and side marker lamps, white lamps front, gravel splash guard in the wheel area

QUICK RUNNER VERSION GERMANY

1.069,- 220 7101	40 km/h-version behind tractors: 2-line airbrake system, 70 mm axes with EG- brake test 300x80/8 hole, underride guard, mudguards, quick runner lighting system, 7-pole, 24V, axes with man. linkage adjuster and membran cylinder, gravel splash guard in the wheel area, tyres 215/75 R 17.5 (18) tbl.
-------------------------	---

QUICK RUNNER VERSIONS GERMANY

1.746,- 220 7201 **60 km/h version** behind tractors: 2-line brake 80 mm axes, 350x80/8 hole, spindle brake, bugle over 25 km/h, underride guard, mudguards on the rear wheels, quick runner lighting system, 7-pole, 24V, axes with man. linkage adjuster and membran cylinder, gravel splash guard in the wheel area, tyres 245/70 R 17.5 (18) tbl.

6.260,- 220 7301 ***80 km/h version** behind tractors: 2-line brake working onto all four wheels, with ALB, ABS, 24 Volt, 80 mm axes with EG-brake test, 350x80/8 hole, spindle brake, bugle over 25 km/h, underride guard, mudguards on the rear wheels, fog tail lamps, quick runner lighting system, 7-pole, 24 voltage, axes with autom. linkage adjuster and membran cylinder, tyres 245/70 R 17.5 (18) tbl. gravel splash guard in the wheel area

Other lighting systems see page 3

0,- 220 7810 Standardization of types on 10 to permissible gross weight (no 6 month security inspection - see page 3)

CAUTION: Required for non agriculture tractors:

424,- 220 7510 Contour and side marker lamps

878,- 220 7520 AGS - automatic linkage adjuster for airbraked axes

TYRES INSTEAD OF STANDARD TYRES:

378,- 220 8200 245/70 R 17.5

9,- 220 8280 355/60 R 18 MPT (16)

510,- 220 8900 Spare wheel mounting (on the forehead wall)

SUPPORT FACILITIES:

91,- 220 6110 Support wheel with angular gear

145,- 220 6120 Support winch mech. max. 1000 kg support weight

323,- 220 6140 Semi trailer support winch with 2 speeds

512,- 220 6130 Hydraulic support foot with protected double-acting cylinder, pipe in pipe guide to accommodate the axial forces, with locking block for double-acting cylinder as standards (no shut-off valves required)

* With these vehicles you are requested to submit the data accord. to the data sheet page 93 immediatley when generating the order!

