

# BRANTNER

## TWO-AXLE PLATFORM CARRIAGE **PW 8000**

### 10 YEARS WARRANTY ON CHASSIS FRAME

**Perm. gross weight: 8 t, Payload: approx. 6 t**  
**Platform size:**  
**5000 x 2200 mm**

Technical data approx.:

Permissible gross weight	8000 kg
Dead weight:	1850 kg
Platform size inside:	5000 x 2200 mm
Overall length:	<b>6900 mm</b>
Overall width:	2200 mm
Track:	1650 mm
Axle cross section:	70 mm
Platform height:	1080 mm
Tyres:	11.5/80 - 15.3 (10) with tube
KLK-diameter:	1050 mm

Euro without

VAT	Art. Nr.	
		<b>Basic price PW 8000</b>
<b>o.MP</b>		Germany vehicle certificate 25 km/h (not required for agriculture)

#### CHASSIS :

**79,-** 630 1110 Trailer coupling 25 km/h - 8 to gross weight

**198,-** 630 1190 Gravel splash guard in the wheel area

#### PLATFORM:

**323,-** 630 2300 Steel base 5 mm instead of 4 mm

**760,-** 630 2151 Platform extension on 5500 mm

**874,-** 630 2154 Platform extension on 6000 mm

**991,-** 630 2156 Platform extension on 6500 mm

**659,-** 630 2142 Platform broadening on max. 2550 mm

**2.907,-** 630 2440 Platform base made of norm grating (area load 1480 kg/m<sup>2</sup>) Platform width 2400 mm. (length only in 1 meter-leaps available)

**1.725,-** 630 2450 Folding frame for round ball transportation

**20,-** 630 2455 Eyes for lashing straps behind frame per piece

#### BODY:

**1.156,-** 630 3242 Steel sideboards 500 mm with corner rungs, max. Width inside 2,41 m \*)

**1.156,-** 630 3140 Steel attachment boards with corner rungs 500 mm \*)

**246,-** 630 3720 Rabbet made of flat steel for box protection

**321,-** 630 3721 Front assault gate forced up approx. 1800 mm

#### BRAKING SYSTEMS:

**762,-** 630 5610 2-line airbrake system instead of overrunning moving automatism for 25 km/h

**1.526,-** 630 5620 2-line airbrake system additional to overrunning moving automatism for 25 km/h

**208,-** 630 5640 Combined 1-and 2-line airbrake system instead of 2-line airbrake system f. 25 km/h

**359,-** 630 5710 Rear connection with 2-line airbrake system

**280,-** 630 5730 Rear connection with 1-line airbrake system

**426,-** 630 5740 Rear connection with 1-and 2-line airbrake system

**398,-** 630 5750 ALB (automatic load-dependent brake force control) of the 2-line airbrake system (if not included in the quick runner packet)

#### QUICK RUNNER VERSIONS AUSTRIA

**1.841,-** 630 7100 **40 km/h version:** behind agriculture tractors: 2-line brake, with ALB, 70 mm axes, brakes 300x60/6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 12.5/80 - 18 (10) with tube, contour and side marker lamps, lateral underride guard, white lamps front

#### Standard equipment:

Chassis: Cranked frame made of closed C- and G-pressed sections 8 mm, 40 km/h axes with leaf spring and spring support

Platform: Platform made of 4 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), lateral right-angled folding for high stability

Sideboards: Without sideboards, without attachment boards

Brake installation: Overrunning brake with moving automatism, fourwheel braked

Electricity: 12 voltage light and indicator system, socket rear

Paintwork: Dip priming and hot spray painting

Licence: Austria: 10 km/h without type certificate  
Germany: ABE 25 km/h agriculture

Euro without

VAT Art. Nr.

#### QUICK RUNNER VERSIONS AUSTRIA

**6.383,-** 630 7200 **\*60 km/h version:** behind agriculture tractors: 2-line brake working onto all four wheels, with ALB, AGS, ABS 24V, 70 mm axes, brakes 300x80/6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16), contour and side marker lamps, lateral underride guard, white lamps front

**7.113,-** 630 7320 **\*80 km/h version** behind agriculture tractors: 2-line brake working onto all four wheels, with ALB, AGS, ABS 24V, 70 mm axes, brakes 300x80/6, underride guard, mudguards, fog tail lamp, quick runner lighting system, 7-pole, 24 voltage, tyres 355/60 R 18 MPT (16), contour and side marker lamps, lateral underride guard, white lamps front

#### QUICK RUNNER VERSIONS GERMANY

**989,-** 630 7103 **40 km/h version:** behind agriculture tractors: moving automatism brake, without airbrake system, 70 mm axes, wheel brake 300x60/6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 12.5/80 - 18 (10)

**1.983,-** 630 7101 **40 km/h version** behind agriculture tractors: 2-line airbrake system, with ALB, without ABS, 70 mm axes 300x80/6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 12.5/80 - 18 (10)

**2.549,-** 630 7201 **\*60 km/h version** behind agriculture tractors: 2-line airbrake system, without ALB, without ABS, 70 mm axes 300x80/6, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16)

**6.585,-** 630 7321 **\*80 km/h version** behind agriculture tractors; 2-line brake working onto all four wheels, with ALB, AGS, ABS 24V, 70 mm axes, brakes 300x80/6, underride guard, mudguards, fog tail lamp, quick runner lighting system, 7-pole, 24 voltage, tyres 355/60 R 18 MPT (16)

**CAUTION:** Required for non agriculture tractors:

**424,-** 630 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)

**877,-** 630 7520 AGS-automatic linkage adjuster for airbraked axes (not required in connection with agriculture tractors)

#### TYRES INSTEAD OF STANDARD TYRES:

**404,-** 630 8130 13.0/75 - 16 (10)

**512,-** 630 8150 15.0/55 - 17 (10)

**730,-** 630 8240 12.5/80 - 18 (12)

**1.227,-** 630 8290 340/65 R 18 (16) Mich. steel case

**911,-** 630 8280 355/60 R 18 MPT (16)

**510,-** 630 8900 Spare wheel mounting

\* With these vehicles you are requested to submit the data according to the data sheet Page 93 immediately when generating the order!