

BRANTNER

TWO-AXLE PLATFORM CARRIAGE **PW 11000**

10 YEARS WARRANTY ON CHASSIS FRAME

Perm. gross weight: 11 to, Payload: ca. 9 to
Platform size:
5000 x 2200 mm

Technical data approx:

Permissible gross weight:	11000 kg
Dead weight:	2020 kg
Platform size inside:	5000 x 2200 mm
Overall length:	6900 mm
Overall width:	2200 mm
Track:	1650 mm
Axle cross section:	70 mm
Platform height:	1180 mm
Tyres:	12.5/80 - 18 (12) with tube
KLK-diameter:	1050 mm

Euro without

VAT	Art. Nr.	
10.110,-	631 0000	Basic price PW 11000
o.MP		Germany vehicle certificate 25 km/h (not required for agriculture)

CHASSIS:

79,-	631 1110	Trailer coupling 25 km/h - 8 to gross weight
198,-	631 1190	Gravel splash guard in the wheel area

PLATFORM:

323,-	631 2300	Steel base 5 mm instead of 4 mm
760,-	631 2151	Platform extension on 5500 mm
874,-	631 2154	Platform extension on 6000 mm
991,-	631 2156	Platform extension on 6500 mm
1.237,-	631 2167	Platform extension on 7000 mm
659,-	631 2142	Platform broadening on max. 2550 mm
2.906,-	631 2440	Platform base made of norm grating (area load 1480 kg/m²) Platform width 2400 mm. (length only in one meter leaps available)

1.725,-	631 2450	Folding frame for round ball transport
20,-	630 2455	Eyes for lashing straps behind frame per piece

BODY:

1.156,-	631 3242	Steel sideboards 500 mm with corner rungs, max. Width inside 2,41 m *)
1.156,-	631 3140	Steel attachment boards with corner rungs 500 mm *)
246,-	630 3720	Rabbit made of flat steel to box protection
321,-	630 3721	Front assault gate forced up approx. 1800 mm

BRAKING SYSTEMS:

208,-	631 5640	Combined 1- and 2-line airbrake systems instead of 2-line airbrake system for 25 km/h
359,-	631 5710	Rear connection with 2-line airbrake system
280,-	631 5730	Rear connection with 1-line airbrake system
426,-	631 5740	Rear connection with 1- and 2-line airbrake system
398,-	631 5750	ALB (automatic load-dependent brake force control) of the 2-line airbrake system (if not included in the quick runner packet)

QUICK RUNNER VERSIONS AUSTRIA

2.958,-	631 7100	40 km/h version behind agriculture tractors: 2-line airbrake system, with ALB, without ABS, 70 mm axes, brakes 300x90/8, underride guard, mudguards, quick runner lighting system, 7-pole, 12 V, tyres 355/60 R 18 MPT (16), lat. underride guard
8.806,-	631 7200	60 km/h version behind agriculture tractors: 2-line brake with ALB, AGS, ABS, 70 mm axes, brakes 350x80/8, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16), lateral underride guard

Standard equipment:

Chassis:	Cranked frame made of closed C-and G-pressed section 8 mm, axes with leaf spring and spring support, Y-forked draw-bar for small turning radius
Platform:	Platform made of 4 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), lateral right-angled folding for high stability
Sideboards:	Without sideboards, without attachment boards
Brake installation:	2-line airbrake system, fourwheel brake
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and hot spray painting
Licence:	Austria: 25 km/h type certificate for agriculture Germany: ABE 25 km/h agriculture

Euro without

VAT Art. Nr.

QUICK RUNNER VERSIONS AUSTRIA

9.502,-	631 7320	*80 km/h version behind agriculture tractors: 2-line brake, with ALB, AGS, ABS 24V, 70 mm axes, brakes 350x80, underride guard, mudguards, fog tail lamp, quick runner lighting system, 7-pole, 24 voltage, tyres 355/60 R 18 MPT (16), lateral underride guard
---------	----------	--

QUICK RUNNER VERSIONS GERMANY

1.048,-	631 7101	40 km/h version behind agriculture tractors: 2-line airbrake system, without ALB, without ABS, 70 mm axes, 300x90/8, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16)
1.156,-	631 7201	*60 km/h version behind agriculture tractors: 80 mm axes with EG brake test, otherwise as above, however admission on 60 km/h

7.139,-	631 7321	*80 km/h version behind agriculture tractors: 2-line airbrake system working onto all four wheels, with ALB, AGS, ABS 24V, 70 mm axes, brakes 350x80, underride guard, mudguards, fog tail lamp, quick runner lighting system, 7-pole, 24 voltage, tyres 355/60 R 18 MPT (16)
---------	----------	--

o.MP	631 7810	Standardization of types of 10 to perm. gross weight (no six-month security inspection - see Page 3)
-------------	----------	--

CAUTION: Required for non agriculture tractors:

424,-	631 7510	Contour lamps and side marker lamps (not required in connection with agriculture tractors)
877,-	631 7520	AGS-automatic linkage adjuster for airbraked axes (not required in connection with agriculture tractors)

TYRES INSTEAD OF STANDARD TYRES:

182,-	631 8280	355/60 R 18 MPT (16)
498,-	631 8290	340/65 R 18 (16) Mich. steel case
664,-	631 8310	285/70 R 19.5
-320,-	631 8130	Price reduction: 13.0/75 - 16 (10)
510,-	631 8900	Spare wheel mounting

*** With these vehicles you are requested to submit the data according to the data sheet Page 93 immediately when generating the order!**