

# BRANTNER

## TWO-AXLE THREE-SIDED TIPPER Z 11045 XXL

### 10 YEARS WARRANTY ON CHASSIS FRAME

**Perm. gross weight: 11 t, Payload: 8,2 t**  
**Platform size outside:**  
**4550 x 2220/2320 x 600 + 600 mm**  
**Swing board left, right, rear**  
**2-line airbrake**

#### Technical data approx.:

Perm. gross weight:	11000 kg
Dead weight:	2790 kg
Platform size inside:	<b>4480 x 2150/2250 mm</b>
Overall length:	6550 mm
Overall width:	2420 mm
Steel sideboards:	600 mm
Attachment boards:	600 mm
Track:	1800 mm
Spring distance:	1250 mm
Axle cross section:	70 mm
Platform height:	1230 mm
Tyres:	12.5/80 - 18 (12)
Tipping cylinder stage:	3 / 4
Stroke length:	1600/1600
KLK-diameter:	1050 mm
Cyl. diameter + 1 cyl.	75/90/105
Cylinder diameter with	60/75/90/105
Max. operating pressure:	200 bar
Tipping angle lateral/	45/45 degrees
Required amount of oil:	12/18 l

#### Euro without

VAT Art. Nr.

**14.869,-** 402 0010 **Basic price with 1 lifting cylinder Z 11045 XXL 25 km/h with 2-line airbrake system**

**15.537,-** 402 0000 **Basic price with 2 lifting cylinder Z 11045/2 XXL 25 km/h with 2-line airbrake system**

o. MP 402 0100 Germany: Vehicle certificate 25 km/h (not required for agriculture) net

#### Special equipment against extra charge

#### CHASSIS:

<b>Series</b> 402 1110 Trailer coupling 25 km/h - 8 to gross weight
<b>206,-</b> 402 1115 Trailer coupling over 25 km/h - 11 t gross weight. (G)
<b>945,-</b> 402 1140 Autom. trailer coupling (with cyl. 1600 mm lift)
<b>198,-</b> 402 1190 Gravel splash guard in the wheel area

#### PLATFORM:

<b>700,-</b> 402 2174 4480 x 2410 mm inside
<b>1.519,-</b> 402 2130 5040 x 2150 / 2250 mm inside
<b>2.208,-</b> 402 2175 5080 x 2410 mm inside

#### BODY:

<b>979,-</b> 402 3200 2 <sup>nd</sup> set steel attachment boards 400 mm *)
<b>1.156,-</b> 402 3210 2 <sup>nd</sup> set steel attachment boards 500 mm *)
<b>1.323,-</b> 402 3220 2 <sup>nd</sup> set steel attachment boards 600 mm *)
<b>293,-</b> 402 3230 3 <sup>rd</sup> steel attachment board 500 mm only rear
<b>309,-</b> 402 3420 Steel attachment board 2,5 mm instead 2 mm per set
<b>121,-</b> 402 3120 Sideboard lifting springs left and right
<b>300,-</b> 402 3370 Collapsible attachment boards le + ri (Platform 2320 mm)
<b>71,-</b> 402 3450 Tension chains (1 set per set walls)
<b>131,-</b> 402 3440 Set corner chains
<b>90,-</b> 402 3480 Additional grain slide/ piece
<b>41,-</b> 402 3490 Potato slide (450 mm wide)
<b>78,-</b> 402 3596 View grille (perforated sheet) over the overall width instead of front attachment board
<b>136,-</b> 402 3598 View grille (perforated sheet) between stanchions with sheet metal cover
<b>61,-</b> 402 3460 Discharge channel not lockable
Discharge channel with additional fine dosing
<b>142,-</b> 402 3470 for grain slide

#### Standard equipment:

Chassis:	Cranked frame made of C-sections and G-pressed sections 8 mm, cross stiffening, trailer coupling (in Austria at single approving only for using inside factory), axles with leaf spring and spring support, Y-forked draw-bar
Platform frame:	Closed U-trapezoidal tipping frame JUMBO
Platform:	Conical platform with <b>5 mm steel plate base</b> folded from one piece to all four sides, no weld seam (foil seam fusion), patented self-cleaning platform edge
Sideboards:	Steel sideboards 600 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 6 lateral und 4 rear, plugged corner stanchions, swing board left/right and rear, with central locking lever and closing hook for 30 mm latching range, large closures, grain slide with adjusting lever
Swing attachments:	1 <sup>st</sup> set steel attachment boards 600 mm high, with attachment corner stanchions
Tipping facility:	Ball tipping mountings with conical socket, 3/4-stage lifting cylinder, 1600 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling and shut-off valves, automatic stroke limitation
Brake installation:	2-line airbrake system
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity-primed sideboards, superstructure HB-green
Licence:	Austria: Type certificate 25 km/h agriculture Germany: Operating permit 25 km/h agriculture

#### Euro without

VAT Art. Nr.

#### BODY :

<b>317,-</b> 402 3500 Attachment triangles 300 mm high front and rear
<b>1.960,-</b> 402 3515 <b>Tarpaulin body with roll-up tarpaulin</b> , consisting of: Attachment triangles 300 mm front and rear, folding-type tarpaulin bar, tarpaulin rolled from right to left with aluminium slat and operating platform + railing at the face end (f. serial platforms)
<b>2.114,-</b> 402 3511 Tarpaulin body with roll-up tarpaulin design as above, but: plane rolled from left to right (access ladder right)
<b>293,-</b> 402 3520 Hydraulic lateral swing sideboard plug-type unlocking left and right
<b>370,-</b> 402 3525 Upon subsequent delivery
<b>1.023,-</b> 402 3530 Hydraulic swing sideboard unlocking rear
<b>3.214,-</b> 402 3540 Hydraulic lateral 180° sideboard opening and closing (additional double-acting control unit required), per side
<b>415,-</b> 402 3570 Stable chute lateral approx. 360 mm high per side, for opening jointly with lateral swing sideboard unlocking
<b>250,-</b> 402 3410 Sideboard stiffening left and right per set
<b>-1.088,-</b> 402 3400 Price reduction: Supply without swing attachments
<b>-168,-</b> 402 3260 Price red.: Sideboard 500 mm instead of 600 mm
<b>-136,-</b> 402 3360 Price red.: Attachment board 500 mm instead 600

#### TIPPING INSTALLATION:

Lifting cylinder 75/90/105/120 - 1800 mm, oil quantity, per cylinder approx 14 l, tipping angle. ° 45/49

<b>104,-</b> 402 5325 with 1 cylinder
Lifting cylinder 60/75/90/105 - 1800 mm, oil quantity per cylinder approx. 11 l, tipping angle approx. °45/49
<b>140,-</b> 402 5311 with 2 cylinders
<b>4.092,-</b> 402 5160 High tipping installation (approx. 750 mm higher, additional oil quantity required approx. 8 l) with own connection
<b>410,-</b> 402 5200 Rear hydraulic connection

Euro without

VAT Art. Nr.

### SILAGE BODIES:

**3.130,-** 402 4120 Silage body with hydraulic rear board 1500 mm, grain tight, (with double-acting cylinder), including 2<sup>nd</sup> swing attachment (500mm), approx 15 m<sup>3</sup>, rear board made of 4 mm steel plate, with grain slide, with plug-type rear hydraulic connection, **view grille** (perforated sheet), **4-stage lifting cylinder 1800 mm**

**3.733,-** 402 4136 Silage body with hydraulic rear board 1800 mm, grain tight, (with double-acting cylinder), including 2<sup>nd</sup> swing attachment (600 mm), approx. 18 m<sup>3</sup>, rear board made of 4 mm steel plate, with grain slide, with plug-type rear hydraulic connection, view grille (perforated sheet) 4-stage lifting cylinder 1800 mm lift

**342,-** 402 3234 Additional lower rear board with grain slide and corner stanchions for 500 mm height, with closures

**293,-** 402 3235 Additional 1<sup>st</sup> attachment board 500 mm rear with corner stanchions and closures

**359,-** 402 3238 Additional lower rear board with grain slide and corner stanchions for 600 mm height with closures

**309,-** 402 3237 Additional 1<sup>st</sup> attachment board 600 mm rear with corner stanchions and closures

402 3512 **Tarpaulin body with roll-up tarpaulin in comb. with hydraulic rear wall**  
**LOOK AT PAGE 45**

**162,-** 402 3513 Supports for hydraulic rear wall (supports left and right to support the hydraulic rear wall with uppermost attachment wall folded down)

### BRAKING SYSTEMS:

**208,-** 402 5640 Combined one and two-line airbrake system instead of 2-line airbrake system for 25 km/h

**359,-** 402 5710 Rear connection with 2-line airbrake system

**280,-** 402 5730 Rear connection with 1-line airbrake system

**426,-** 402 5740 Rear connection with 1-und 2-line airbrake system

**510,-** 402 5741 Rear connection for combined one and two-line airbrake with one-line trailer control valve

**398,-** 402 5750 ALB (if not included in the quick runner packet)

### QUICK RUNNER VERSIONS AUSTRIA

**2.402,-** 402 7100 **40 km/h-version** behind agriculture tractors: 2-line airbrake system with **ALB**, 70 mm axes, underride guard, mudguards, licence plate lighting, tyres 355/65 R 18 MPT (16), contour and side marker lamps, white lamps front, gravel splash guard in the wheel area

**8.249,-** 402 7200 **60 km/h-version** behind agriculture tractors: 2-line airbrake system with **ALB, AGS, ABS, 70 mm axes**, underride guard, mudguards, licence plate lighting, tyres 355/60 R 18 MPT (16), contour and side marker lamps, white lamps front, gravel splash guard in the wheel area



EURO without

VAT Art. Nr.

### QUICK RUNNER VERSIONS AUSTRIA

**8.945,-** 402 7300 **80 km/h-version** behind agriculture tractors: 2-line airbrake system with **ALB, AGS, ABS (24V), 70 mm axes**, underride guard, mudguards, fog tail lamp, quick runner lighting system, tyres 355/60 R 18 MPT (16), contour and side marker lamps, white lamps front, gravel splash guard in the wheel area

### QUICK RUNNER VERSIONS GERMANY

**1.052,-** 402 7101 **40 km/h-version** behind agriculture tractors: 2-line airbrake system, without ALB, without ABS, 70 mm axes with EG-brake test 300x90/8, spindle brake, forked draw-bar over 25 km/h, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16)

**1.156,-** 402 7201 **60 km/h-version** behind agriculture tractors: 80 mm axes, all others as above, however admission on 60 km/h

**7.139,-** 402 7321 **80 km/h version** behind agriculture tractors: 2-line airbrake system, with ALB, ABS (24 V), 70 mm axes, underride guard, mudguards, fog tail lamp quick runner lighting system, 7-pole, 12 voltage, tyres 355/60 R 18 MPT (16), gravel splash guard in the wheel area

**0,-** 402 7810 Standardization of types on 10 to permissible gross weight (no six month security inspection)

**Other lighting systems see page 93**

**CAUTION: Required for non agriculture tractors**

**424,-** 401 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)

**878,-** 401 7520 AGS - automatic linkage adjuster for airbraked axes

### TYRES INSTEAD OF STANDARD TYRES:

**182,-** 401 8280 355/60 R 18 MPT (16)

**498,-** 401 8290 340/65 R 18 (16) Mich. Steel case.

**664,-** 402 8310 285/70 R 19.5

**-326,-** 401 8130 Price reduction: 13.0/75 -1 6 (10)

### None-retrofit tyres

**1.440,-** 402 8184 505/50 R 17 MPT, with double hump-security rim (corresponds 16 pr), to 90 km/h suitable, track 1920 mm, axle cross section 80 mm

**510,-** 401 8900 Spare wheel mounting

