

BRANTNER

TWO-AXLE THREE-SIDED TIPPER Z 15 051/2 XXL

10 YEARS WARRANTY ON CHASSIS FRAME

Permissible gross weight: 15 to
Payload: approx. 11,1 to
Platform size outside:
5110 x 2320 x 600 + 600 mm
Swing board left + right + rear
40 km/h 2-line airbrake

Technical data approx.:

Perm. gross weight:	15000 kg
Dead weight:	3860 kg
Platform size inside:	5040 x 2250 mm
Overall length:	7060 mm
Overall width:	2470 mm
Steel sideboards:	600 mm
Attachment boards:	600 mm
Track:	1800 mm
Spring distance:	1250 mm
Axle cross section:	90 mm
Platform height:	1350 mm
Tyres:	385/65 R 22.5 MZA remould
Number of holes in rim:	10
Tipping cylinder stage:	3
Stroke length:	1600 mm
KLK-diameter:	1050 mm
Cyl. diameter 2 cyl.:	75/90/105
Max. operating pressure:	200 bar
Tipping angle lateral/vertical:	45/46 Degrees
Required amount of oil:	22 l

Euro without

VAT	Art. Nr.	
18.843,-	404 0000	Basic price with 2 lifting cyl. Z 15051/2 XXL 25 km/h version agriculture Austria
20.562,-	404 0001	Basic price with 2 lifting cylinders Z 15051/2 XXL 40 km/h version agriculture Austria 2-line airbrake, with ALB, 90 mm axes 400x120/10, mudguards, gravel splash guard in the wheel area, contour- and side marker lamps, white lamps front, mechanical linkage adjuster, underride guard, ground clearance max. 550 mm
19.156,-	404 0002	Basic price with 2 lifting cylinders Z 15051/2 XXL 40 km/h version agriculture Germany 2-line airbrake, without ALB, 90 mm axes 400x80/10, mudguards, gravel splash guard in the wheel area, quick runner lighting system, 7-pole, 12V, mechanical linkage adjuster, underride guard, potato slide

Special equipment against extra charge

CHASSIS:

Serie 404 1110	Trailer coupling 25 km/h-8 t gross weight with adapt.
612,- 404 1130	Automatic trailer coupling
0,- 404 1190	Gravel splash guard in the wheel area

BODY:

1.323,- 404 3210	2 nd set steel attachment boards 500 mm *)
1.323,- 404 3220	2 nd set steel attachment boards 600 mm *)
293,- 404 3230	3 rd steel attachment board 600 mm only rear
Series 404 3450	Tension chains (1 set per set walls)
121,- 404 3425	Sideboard lifting springs left + right
211,- 404 3587	Outrigger struts for lateral sideboards
90,- 404 3480	Additional grain slide/piece
Series 404 3490	Potato slide (450 mm wide)
1.336,- 404 3599	Split sideboard + attachment board left and right with plug-in centre stanchions
78,- 404 3596	View grille (perforated sheet) over the overall width instead of front attachment board
136,- 404 3598	View grille (perforated sheet) between stanchions with sheet metal cover

Standard equipment:

Chassis:	Cranked frame made of closed C-sections and G-pressed sections 8 mm, cross stiffening, 40 km/h axes with leaf spring and spring support, shunting coupling for using inside factory
Platform frame:	Closed U-trapezoidal tipping frame JUMBO
Platform:	Platform with 5 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion), pat. self-cleaning platform edge
Sideboards:	Steel sideboards 600 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 7 lateral and 4 rear, plugged corner stanchions, swing board left/right and rear, with central locking lever and closing hook for 30 mm latching range, large closures, potato slide with adjusting lever
Swing attachments:	1 st set steel attachment boards 600 mm high, with attachment corner stanchions
Tipping facility:	Ball tipping mountings with conical socket, 4-stage lifting cylinder, 1600 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling and shut-off valve, automatic stroke limitation
Brake installation:	2-line airbrake system, axes with manual linkage adjusters and diaphragm cylinders
Electricity:	12 voltage light and indicator system, 7-pole, socket rear
Paintwork:	Dip priming and 2 component acrylic paint-hot spray painting, cavity-primed sideboards, superstructure HB-green
Licence:	Austria: Type certificate 25 km/h agriculture Germany: 40 km/h vehicle certificate agriculture

Euro without

VAT	Art. Nr.	
BODY:		
61,- 404 3460	Discharge channel not lockable	
	Discharge channel with additional fine dosing for potato slide	
205,- 404 3475		
317,- 404 3500	Attachment triangles 300 mm high front and rear	
1.960,- 404 3515	Tarpaulin body with roll-up tarpaulin , consisting of: Attachment triangles 300 mm front & rear, folding-type tarpaulin bar, tarpaulin rolled from right to left with aluminium slat and operating platform with railing at the face end (f. serial platf.)	
2.114,- 404 3511	Tarpaulin body with roll-up tarpaulin as above, only: plane rolled from left to right (access ladder on the right)	
293,- 404 3520	Hydraulic lateral swing sideboard plug-type unlocking left and right	
370,- 404 3525	Upon subsequent delivery	
1.023,- 404 3530	Hydraulic swing sideboard unlocking rear	
3.214,- 404 3540	Hydraulic lateral 180° sideboard opening and closing (additional double-acting control unit required on tractor)	
415,- 404 3576	Stable chute lateral approx. 360 mm high per side, for opening jointly with lateral swing sideboard unlocking	
621,- 404 3577	Stable chute plug-type left and right	
250,- 404 3410	Sideboard stiffening left and right	
-984,- 404 3400	Price reduction: Delivery without swing attachments	
TIPPING INSTALLATION:		
4.092,- 404 5160	High tipping installation (approx. 750 mm higher, additional oil quantity required approx. 8 l) with own connection	
410,- 404 5200	Rear hydraulic connection	
	Lifting cylinder 60/75/90/105 - 1800 mm, oil quantity approx. 11 l per cylinder, tipping angle approx. ° 45/49	
140,- 404 5311	with 2 cylinders:	

Euro without
VAT Art. Nr.

SILAGE BODIES:

3.764,- 404 4136 Silage body with hydr. rear wall 1800 mm, grain-tight, (with double-acting cylinders), including 2nd swing attachment (600 mm), approx. 20 m³, rear wall made of 4 mm steel plate, with potato slide, with plug-type rear hydraulic connection, view grille (perforated sheet), 4-stage lifting cylinder 1800 mm lift,

359,- 404 3238 Additional lower rear board with potato slide and corner stanchions, 600 mm height with closures

309,- 404 3237 Additional 1st attachment board 600 mm rear + corner stanchions + closures

404 3512 **Tarpaulin body with roll-up tarpaulin in combination with hydraulic rear wall**
LOOK AT PAGE 45

162,- 404 3513 Supports for hydraulic rear wall (supports left and right to support the hydraulic rear wall with uppermost attachment wall folded down)

STABILATOR - BODY:

521,- 404 3650 Stabilator walls in particularly stable design 3 mm with smooth inside surface, height 1500 mm, only suitable for swing operation, potato slide 570 x 270 mm, **(Three-sided tipper with the stability of a dumper)**

139,- 404 3460 Discharge channel cannot be locked

2.629,- 404 3660 Hydraulic rear wall opening **double-acting** for stabilator-body of 4 mm steel plate, with potato slide and with plug-type rear hydraulic connection, 4-stage lifting cylinder 1800 mm lift

Steel attachment walls in grain-tight design (with hydraulic rear wall compounding needed, close to about 1,80 m)

1002,- 404 3670 300 mm high

1.323,- 404 3672 500 mm high

1.587,- 404 600 mm high

Mulch plug-type walls for front wall (perforated sheet) and side walls from the front to just before the mounting of the hydraulic rear wall opening

824,- 404 3682 500 mm high

989,- 404 600 mm high

235,- 404 3690 Thick sheets in the area of rear board mounting for grain transport

1.748,- 404 3700 Stabilator-walls height 600 mm out of Hardox 400, 4 mm particularl stalbe version

2.488,- 404 2350 Hardox-steel base 5 mm instead of serial base

BRAKING SYSTEMS:

796,- 404 5640 Combined one and two-line airbrake system instead of two-line airbrake system for 25 km/h

359,- 404 5200 Rear connection for two-line airbrake system

426,- 404 5740 Rear connection + one & two-line airbrake system

510,- 404 5741 Rear connection for combined one and two-line airbrake with one-line trailer control valve

398,- 404 5750 ALB (automatic load-dependent brake force control) of the 2-line airbrake system, if not included in the quick runner packet

Euro without
VAT Art. Nr.

QUICK RUNNER VERSIONS AUSTRIA:

4.804,- 404 7200 **60 km/h-version** behind agriculture tractors: 2-line airbrake system with ALB, ABS, 90 mm axes, **brakes 400x120/10**, tyres 385/65 R 22.5 Idw. remould 80 km/h, gravel splash guard in the wheel area, quick runner lighting system

QUICK RUNNER VERSIONS GERMANY:

497,- 404 7201 **60 km/h version** behind agriculture tractors: 2-line airbrake, 90 mm axes 400x120/10, underride guard, mudguards, quick runner lighting system, 7-pole, 12 voltage, axes with manual linkage adjusters and diaphragm cylinders, tyres 385/65 R 22.5 Idw. remould XZA, gravel splash guard in the wheel area

Other lighting systems see page 93

CAUTION: Required for non agriculture tractors:

424,- 404 7510 Contour lamps and side marker lamps (not required in connection with agriculture tractors)

1.175,- 404 7520 AGS - automatic linkage adjuster for airbraked axes

TYRES INSTEAD OF STANDARD TYRES:

0,- 404 8351 385/65 R 22.5 Y1 remould

1.180,- 404 8370 385/65 R 22.5 LORRY la new

510,- 404 8900 Spare wheel mounting

