

!!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!!

BRANTNER
TANDEM THREE-SIDED TIPPER

TA 10.041 Classic-Line

10 YEARS WARRANTY ON CHASSIS FRAME

Perm. gross weight: 10 to, Payload ca. 7 to
Platform size inside:
4140 x 2150 x 500 + 500 mm
25 km/h

Technical data approx.:

Perm. gross weight:	10000 kg
	from 1.10.2006 without airbrake system max 8000 kg pem. gross weight
Dead weight:	2190 kg
Platform size inside:	4070 x 2080 mm
Overall length:	5410 mm
Overall width:	2260 mm
Steel sideboards:	500 mm
Attachment boards:	500 mm
Track:	1550 mm
Axle cross section:	70 mm
Platform height:	1010 mm
Tyres:	11.5/80 - 15.3 (10)
Tipping cylinder stage	3
Stroke length:	1400 mm
Cylinder diameter:	75 / 90 / 105 mm
Max. operating pressure:	200 bar
Tipping angle lateral/vertical	45/45 degrees
Required amount of oil	8,5 l

Standard equipment:

Chassis:	V-frame made of C-pressed section frame 6 mm, shunting coupling for using inside factory, tandem axle with leaf spring mounted under axle, control arm compensation and spring support, towing facility: (D/H: 40/31 mm)
Platform frame:	V-trapezoidal tipping frame
Platform:	Platform with 5 mm steel plate base folded from one piece to all four sides, no weld seam (foil seam fusion, patented self-cleaning platform edge)
Sideboards:	Steel sideboards 500 mm high with skirting board 70 mm, cavity priming, sideboard hinges: 5 lateral and 4 rear, plugged corner stanchions, pivot board rear with central locking lever grain slide, sideboard lifting springs left + right
Swing attachments:	1 st set steel attachment boards 500 mm high, with attachment corner stanchions, collapsible attachment boards
Tipping facility:	Ball tipping mounting with conical socket, 3-stage lifting cylinder 1400 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling, automatic stroke limitation
Brake installation:	Austria: Changing brake Germany: 2-line airbrake system
Support:	Support wheel, collapsible and adjustable in height
Electricity:	12 Volt light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity primed sideboards, superstructure HB-green
Licence:	Austria: Type certificate 25 km/h agriculture Germany: Operating permit 25 km/h agriculture

NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!!

Euro without

VAT Art. Nr.

8.883,- 290 0000 **Basic price for TA 10.041 Export**
25 km/h version Austria
with changing brake

10.338,- 290 0001 **Basic price for TA 10.041 Export**
25 km/h version Germany with two-line airbrake
system

CHASSIS:

Series Trailer coupling 25 km/h

BODY:

Series **sideboard lifting springs left + right**

Series **collapsible attachment boards**

792,- 290 3210 2nd set steel plate attachment boards 500 mm *)

TIPPING INSTALLATION:

40,- 290 5110 Shut-off valve

BRAKES :

1.454,- 290 5615 2-line airbrake (or 1-line airbrake)

1.640,- 290 5640 Combined 1- and 2-line airbrake

342,- 290 5710 Rear connection 2-line airbrake

270,- 290 5730 Rear connection 1-line airbrake

391,- 290 5740 Rear connection combined 1- and 2- line airbrake

Euro without

VAT Art. Nr.

BRAKING SYSTEMS (not for Germany):

726,- 290 5760 Oil hydraulic brake without load adaptation valve x)

1.200,- 290 5765 Oil hydraulic brake with load adaptation valve x)

x) only for in-plant purposes

TYRES INSTEAD OF STANDARD TYRES:

360,- 290 8530 12.5/80 - 15.3 (14)

400,- 290 8130 13.0/75 - 16 AM (10)

909,- 290 8280 355/60 R 18 MPT (16)

NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!!

We can only produce quality tippers for these advantageous net-prices only in large volumes. Please have comprehension, that we can only deliver these tippers with above equipments. This tipper has the same quality standard like other Brantner vehicles, but it's only possible to this price with equipments according to this side. For other equipments please pay attention to other types.