

!!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!!

BRANTNER

TWO-AXLE THREE-SIDED TIPPER

Z 18.051/2 XXL Classic-Line

10 YEARS WARRANTY ON CHASSIS FRAME

**Perm. gross weight: 18 t, payload: ca. 13,5 to
Plateaugröße außen:
5150 x 2480 x 800 + 600 mm
Swing board left, right, rear
2-line airbrake**

Technical data approx.

Perm. gross weight:	18000 kg
Dead weight:	4500 kg
Platform size inside:	5080 x 2410 mm
Overall length:	7200 mm
Overall width:	2550 mm
Steel sideboards:	800 mm
Attachment boards:	600 mm
Track:	2000 mm
Axle cross section:	100 mm
Platform height:	1380 mm
Tyres:	385/65 R 22.5 remould
Tipping cylinder stage	3
Stroke length:	1600 mm
KLK-diameter	1200 mm
Cylinder diameter:	75/90/105 mm
Max. operating pressure	200 bar
Tipping angle lateral/	approx. 45/45 °
Required amount of c	22 l

Standard equipment:

Chassis:	Cranked, closed double-C-pressed section frame, with cross bracing, Y-forked draw-bar until 26 to, 60 km/h axes , with parabola swing 2-layered (as of 2008), suspension support, shunting coupling
Platform frame:	closed U-trapezoidal tipping frame JUMBO
Platform:	Platform with 5 mm steel plate base folded from one piece to all four sides, patented self-cleaning platform edge
Sideboards:	Sideboards 800 mm high, 2,5 mm thick, with sideboard stiffening left and right, cavity priming, sideboard hinges: 7 lateral and 4 rear, bolted corner stanchions, pivot board left/right and rear with central locking lever and closing hook for 30 mm latching range, grain slide, sideboard lifting spring left and right
Swing attachments:	1 st set steel attachment boards 600 mm high, 2,5 mm thick with attachment corner stanchions
Tipping facility:	Ball tipping mounting with socket, 2 pieces 3-stage lifting cylinder 1600 mm, hard-chromed, cardanic mounting, connection line with plug-in coupling, automatic stroke limitation, hydraulic switch-through capability on 2nd tipper
Brake installation:	2-line airbrake system, rear airbrake connection 2-line, axes with manual linkage adjuster and membran cylinder
Electricity:	12 voltage light and indicator system, socket rear
Paintwork:	Dip priming and 2 component acrylic paint hot spray painting, cavity-primed sideboards, superstructure HB-green, gravel splash guard in the wheel area
Traffic licence:	Austria: Type certificate 25 km/h agriculture Germany: Vehicle certificate 60 km/h agriculture

NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!!

Euro without

VAT Art. Nr.

19.298,-	493 0000	Basic price Z 18.051/2 XXL Classic-Line with 2 cyl. 25 km/h version Austria
20.433,-	493 0001	Basic price Z 18.051/2 XXL Classic-Line with 2 cyl. 40 km/h version Austria 2-line airbrake system, with ALB, 100 mm axes, 400x120/10 mudguard, gravel splash guard in the wheel area, contour and side marker lamps, white lamps front, mech. linkage adjuster, underride guard, base distance max. 550 mm
20.368,-	493 0002	Basic price Z 18.051/2 XXL Classic-Line with 2 cyl. 40 or 60 km/h Germany 2-line brake, with ALB, 100 mm axes 400x120/10, mudguard, autom. trailer coupling , mudguard, gravel splash guard in the wheel area, mech. Linkage adjuster, underride guard, potato slide

Special equipment against extra charge

CHASSIS:

612,-	493 1130	Autom. trailer coupling (with 40 km/h necessary) instead of 25 km/h trailer coupling
--------------	----------	--

Euro without

VAT Art. Nr.

BODY:	
Series	sideboard lifting spring left and right
Series	pivot board left and right
317,-	493 3500 Attachment triangles front + rear 300 mm high
476,-	493 3350 Steel attachment boards 800 mm instead of 600 mm
1.217,-	493 3210 2 nd set steel swing attachment boards 500 mm *)
1.217,-	493 3220 2 nd set steel swing attachment boards 600 mm *)
1.960,-	493 3515 Tarpaulin body with roll-up tarpaulin, consisting of: Attachment triangles 300 mm front and rear, folding-type tarpaulin bar, central stake, tensioning straps, tarpaulin rolled from right to left with aluminium slat and operating platform with railing at the face end
596,-	493 1730 BPW-axes, pipe 120 mm, brake 410 x 120 mm instead standard axes square, full material 100 mm, brake 400 x 120 mm
415,-	493 3576 Lateral beet slide height 360 mm per side
621,-	493 3577 Lat. beet slide height 360 mm left & right retoolable
TIPPING INSTALLATION:	
Series	hydraulic switch-through capability
BRAKING SYSTEMS:	
Series	rear airbrake connection 2-line

NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!! NET-PRICES !!!

We can only produce quality tippers for these advantageous net-prices only in large volumes. Please have comprehension, that we can only deliver these tippers with above equipments. This tipper has the same quality standard like other Brantner vehicles, but it's only possible to this price with equipments according to this side. For other equipments please pay attention to other types.